

# ISO 17636-2:2022-09 (E)

## Non-destructive testing of welds - Radiographic testing - Part 2: X- and gamma-ray techniques with digital detectors

---

<b>Contents</b>		<b>Page</b>
Foreword .....		v
1	Scope .....	1
2	Normative references .....	1
3	Terms and definitions .....	2
4	Symbols and abbreviated terms .....	6
5	Classification of radiographic techniques and compensation principles .....	8
5.1	Classification .....	8
5.2	Compensation principles, CP I, CP II or CP III .....	8
5.2.1	General .....	8
5.2.2	Compensation principle I (CP I) .....	8
5.2.3	Compensation principle II (CP II) .....	8
5.2.4	Compensation principle III (CP III) .....	8
5.2.5	Theoretical background .....	9
6	General preparations and requirements .....	9
6.1	Protection against ionizing radiation .....	9
6.2	Surface preparation and stage of manufacture .....	9
6.3	Location of the weld in the radiograph .....	9
6.4	Identification of radiographs .....	9
6.5	Marking .....	9
6.6	Overlap of digital images .....	10
6.7	Types and positions of image quality indicators (IQIs) .....	10
6.7.1	General .....	10
6.7.2	Duplex wire IQIs .....	10
6.7.3	Single wire or step-hole IQIs .....	10
6.8	Evaluation of image quality .....	11
6.9	Minimum image quality values .....	12
6.10	Personnel qualification .....	12
7	Recommended techniques .....	13
7.1	Test arrangements .....	13
7.1.1	General .....	13
7.1.2	Single-wall penetration of plane objects (see Figure 1) .....	14
7.1.3	Single-wall penetration of curved objects with the source outside the object (see Figures 2 to 4) .....	14
7.1.4	Single-wall penetration of curved objects with the source inside the object for panoramic exposure (see Figures 5 to 7) .....	15
7.1.5	Single-wall penetration of curved objects with the source located off- centre and inside the object (see Figures 8 to 10) .....	16
7.1.6	Double-wall penetration and double-image evaluation (DWDI) of pipes with the elliptic technique and the source and the detector outside the object (see Figure 11) .....	17
7.1.7	Double-wall penetration and double-image evaluation (DWDI) with the perpendicular technique and source and detector outside the object (see Figure 12) .....	17
7.1.8	Double-wall penetration and single-image evaluation (DWSI) of curved objects for evaluation of the wall next to the detector (see Figures 13 to 16) .....	18
7.1.9	Penetration of objects with different material thicknesses (see Figure 17 to 19) .....	19

7.2	Choice of tube voltage and radiation source .....	20
7.2.1	X-ray devices up to 1 000 kV .....	20
7.2.2	Other radiation sources .....	21
7.3	Detector systems and metal screens .....	22
7.3.1	Minimum normalized signal-to-noise ratio (SNRN) .....	22
7.3.2	Compensation principle II .....	25
7.3.3	Metal screens for IPs and shielding .....	25
7.4	Alignment of beam .....	25
7.5	Reduction of scattered radiation .....	26
7.5.1	Metal filters and collimators .....	26
7.5.2	Interception of backscattered radiation .....	26
7.6	Source-to-object distance .....	26
7.7	Geometric magnification technique .....	33
7.8	Maximum area for a single exposure .....	34
7.9	Processing .....	34
7.9.1	Scan and read-out of images .....	34
7.9.2	Correction of acquired DDA images .....	35
7.9.3	Bad pixel interpolation .....	35
7.9.4	Image processing .....	35
7.10	Monitor viewing conditions and storage of digital radiographs .....	36
8	Test report .....	36
Annex A (normative) Number of exposures for acceptable testing of a circumferential butt weld .....		38
Annex B (normative) Minimum image quality values .....		43
Annex C (normative) Determination of basic spatial resolution .....		51
Annex D (informative) Determination of minimum grey values for CR practice .....		53
Annex E (informative) Grey values -- General remarks .....		58
Annex F (informative) Considering the detector unsharpness for $f_{min}$ .....		60
Annex G (informative) Calculation of recommended X-ray tube voltages from Figure 20 .....		63
Bibliography .....		64