ISO 17636-2:2022-09 (E)

Non-destructive testing of welds - Radiographic testing - Part 2: X- and gamma-ray techniques with digital detectors

Contents

Page

Foreword v

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 2

4 Symbols and abbreviated terms 6

5 Classificationofradiographictechniquesandcompensationprinciples 8
5.1 Classification 8
5.2 Compensation principles, CP I, CP II or CP III 8
5.2.1 General 8
5.2.2 Compensation principle I (CP I) 8
5.2.3 Compensation principle II (CP II) 8
5.2.4 Compensation principle III (CP III) 8
5.2.5 Theoretical background 9

6 General preparations and requirements 9
6.1 Protection against ionizing radiation 9
6.2 Surface preparation and stage of manufacture 9
6.3 Location of the weld in the radiograph 9
6.4 Identification of radiographs 9
6.5 Marking 9
6.6 Overlap of digital images 10
6.7 Types and positions of image quality indicators (IQIs) 10
6.7.1 General 10
6.7.2 Duplex wire IQIs 10
6.7.3 Single wire or step-hole IQIs 10
6.8 Evaluation of image quality 11
6.9 Minimum image quality values 12
6.10 Personnel qualification 12

7 Recommended techniques 13
7.1 Test arrangements 13
7.1.1 General 13
7.1.2 Single-wall penetration of plane objects (see Figure 1) 14
7.1.3 Single-wall penetration of curved objects with the source outside the object (see Figures 2 to 4) 14
7.1.4 Single-wall penetration of curved objects with the source inside the object for panoramic exposure (see Figures 5 to 7) 15
7.1.5 Single-wall penetration of curved objects with the source located off- centre and inside the object (see Figures 8 to 10) 16
7.1.6 Double-wall penetration and double-image evaluation (DWDI) of pipes with the elliptic technique and the source and the detector outside the object (see Figure 11) 17
7.1.7 Double-wall penetration and double-image evaluation (DWDI) with the perpendicular technique and source and detector outside the object (see Figure 12) 17
7.1.8 Double-wall penetration and single-image evaluation (DWSI) of curved objects for evaluation of the wall next to the detector (see Figures 13 to 16) 18
7.1.9 Penetration of objects with different material thicknesses (see Figure 17 to 19) 19

7.2 Choice of tube voltage and radiation source 20
7.2.1 X-ray devices up to 1 000 kV 20
7.2.2 Other radiation sources 21
7.3 Detector systems and metal screens 22
7.3.1 Minimum normalized signal-to-noise ratio (SNRN) 22
7.3.2 Compensation principle II 25
7.3.3 Metal screens for IPs and shielding 25
7.4 Alignment of beam 25
7.5 Reduction of scattered radiation 26
7.5.1 Metal filters and collimators 26
7.5.2 Interception of backscattered radiation 26
7.6 Source-to-object distance 26
7.7 Geometric magnification technique 33
7.8 Maximum area for a single exposure 34
7.9 Processing 34
7.9.1 Scan and read-out of images 34
7.9.2 Correction of acquired DDA images 35
7.9.3 Bad pixel interpolation 35
7.9.4 Image processing 35
7.10 Monitor viewing conditions and storage of digital radiographs 36

8 Test report 36

Annex A (normative) Number of exposures for acceptable testing of a circumferential butt weld 38

Annex B (normative) Minimum image quality values 43

Annex C (normative) Determination of basic spatial resolution 51

Annex D (informative) Determination of minimum grey values for CR practice 53

Annex E (informative) Grey values -- General remarks 58

Annex F (informative) Considering the detector unsharpness for fmin 60

Annex G (informative) Calculation of recommended X-ray tube voltages from Figure 20 63

Bibliography 64