

ISO 7972:2023-05 (E)

Adhesives - Absorption of water into an adhesive layer using an open-faced specimen and determination of shear strength by secondary bonding

| Contents | | Page |
|---|--|-------------|
| Foreword | | iv |
| Introduction | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Principle | 2 |
| 5 | Apparatus | 2 |
| 6 | Test specimens | 2 |
| 6.1 | Open-faced specimen | 2 |
| 6.1.1 | Cleaning | 2 |
| 6.1.2 | Surface treatment | 2 |
| 6.1.3 | Deposition and control of the adhesive thickness | 2 |
| 6.1.4 | Immersion in water | 3 |
| 6.2 | Specimen for single lap shear test | 3 |
| 6.2.1 | Dimensions and alignment | 3 |
| 6.2.2 | Number of specimens | 3 |
| 6.3 | Accuracy | 3 |
| 7 | Conditioning of test | 4 |
| 8 | Procedure | 4 |
| 8.1 | Immersion in water | 4 |
| 8.2 | Secondary bonding | 4 |
| 8.3 | Tensile shear test | 4 |
| 9 | Precision data | 4 |
| 10 | Calculation and expression of results | 5 |
| 11 | Test report | 5 |
| Annex A (informative) Example of preparation of open-faced specimen | | 6 |
| Annex B (informative) Example of secondary bonding | | 8 |
| Bibliography | | 10 |