

ISO 4268:2000-09 (E)

Petroleum and liquid petroleum products - Temperature measurements - Manual methods

Contents	Page
Foreword	v
Introduction	vi
1 Scope	1
2 Normative references	1
3 Introduction to precautions	1
4 Precautions relating to procedures	2
5 Precautions relating to safety	3
5.1 Introduction	3
5.2 General safety precautions	3
5.3 Special safety precautions	4
6 Equipment	5
7 Portable electronic thermometers (PETs)	5
7.1 Introduction	5
7.2 Accuracy requirements	5
7.3 Sensing elements	5
7.4 Electrical safety	6
7.5 Selection and operation of portable electronic thermometers	6
8 Liquid-in-glass thermometers	9
8.1 General	9
8.2 Accuracy and resolution	9
8.3 Specifications	9
8.4 General requirements for liquid-in-glass thermometers	10
8.5 Periodic checks of liquid-in-glass thermometers	10
8.6 Armoured cases for liquid-in-glass thermometers	11
9 Precautions to be taken when selecting and using liquid-in-glass thermometers	11
9.1 Selection of thermometers	11
9.2 Detection and prevention of errors in liquid-in-glass thermometers	13
9.3 Emergent-stem correction	13
10 Tank sampling methods	13
10.1 Cup-case thermometer	13
10.2 Flushing-case thermometer	14
10.3 Sampling-bottle methods	16
11 Vapour-lock samplers and associated thermometers	16
11.1 Vapour-locks on pressurized tanks	16
11.2 Outline description	16
12 Permanently installed spot thermometers	17
12.1 Angle-stem thermometers	17
12.2 Tank-bottom liquid-in-glass thermometers	19

12.3	Accuracy and resolution	19
13	Bimetal-actuated thermometer with dial	19
13.1	Introduction	19
13.2	Description	19
13.3	Accuracy and resolution	19
14	Procedures	19
15	Liquids in pressurized tanks	19
15.1	Introduction	19
15.2	General principles	20
15.3	Equipment	20
15.4	Procedures for pressurized tanks	20
16	Liquids in vapour-tight tanks	22
16.1	Introduction	22
16.2	General principles	23
16.3	Equipment	23
16.4	Procedure for vapour-tight tanks	23
17	Liquids in non-pressurized non-insulated tanks at or near ambient temperature, or in non- pressurized insulated tanks	24
17.1	Introduction	24
17.2	Equipment	24
17.3	Procedures	24
17.4	Vertical cylindrical fixed-roof tanks	26
17.5	Floating-roof tanks	27
17.6	Horizontal and inclined cylindrical tanks	27
17.7	Rail wagons and road vehicles carrying tanks	27
17.8	Ship and barge cargo tanks	28
18	Liquids in non-pressurized non-insulated tanks at temperatures differing by more than 15 °C from ambient	28
18.1	Introduction	28
18.2	General principle	28
18.3	Equipment	29
18.4	Measurement procedure	29
19	Procedures for the verification of permanently installed tank thermometers	30
19.1	Introduction	30
19.2	Specification of reference thermometer	30
19.3	Verification procedure for vertical cylindrical tanks	30
19.4	Verification procedure for other tanks with non-uniform vertical cross-sectional area	31
20	Procedures for using a permanently installed spot thermometer	31
20.1	Introduction	31
20.2	Location of single-point spot thermometers	31
20.3	Specification of thermometers	31
20.4	Verification of representivity of single-point spot thermometer measurements	31
20.5	Procedure for using single-point spot thermometers	32