

DIN 53508:2024-03 (E)

Testing of rubber - Accelerated ageing

| Contents | | Page |
|--|--|-------------|
| Foreword | | 3 |
| Introduction | | 4 |
| 1 Scope | | 5 |
| 2 Normative references | | 5 |
| 3 Terms and definitions | | 5 |
| 4 Ageing methods | | 5 |
| 5 Test pieces | | 6 |
| 6 Ovens | | 6 |
| 6.1 General | | 6 |
| 6.2 Cell-type oven | | 6 |
| 6.3 Heating oven with natural air circulation | | 7 |
| 6.4 Heating oven with laminar air circulation | | 7 |
| 6.5 Heating oven with turbulent air circulation | | 7 |
| 6.6 Heating oven with forced air circulation | | 7 |
| 6.7 Autoclaves | | 7 |
| 7 Calibration | | 7 |
| 8 Procedure | | 7 |
| 8.1 General | | 7 |
| 8.2 Test conditions | | 8 |
| 8.2.1 General | | 8 |
| 8.2.2 Test conditions for accelerated ageing in air as in subclause 4.1 | | 8 |
| 8.2.3 Test conditions for accelerated ageing in oxygen as in subclause 4.2 | | 8 |
| 9 Expression of results | | 9 |
| 10 Assessment of the results | | 9 |
| 11 Precision | | 10 |
| 12 Test report | | 12 |
| Annex A (normative) Calibration programme | | 14 |
| A.1 Inspection | | 14 |
| A.2 Plan | | 14 |
| Bibliography | | 16 |