

ISO 4917-3:2024-02 (E)

Design of nuclear power plants against seismic events - Part 3: Civil structures

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Seismic event	3
5	Structure analysis	3
5.1	Basic requirements	3
5.2	Modeling	3
5.2.1	General	3
5.2.2	Geotechnical parameters, dynamic subsoil properties	4
5.2.3	Material characteristics (parameters)	4
5.2.4	Effective stiffness	5
5.2.5	Contributing masses	5
5.2.6	Damping	5
5.2.7	Hydrodynamic effects	6
5.3	Analysis methods	6
5.3.1	General requirements	6
5.3.2	Response spectrum method	7
5.3.3	Time history method	7
5.3.4	Frequency domain method	9
5.3.5	Simplified methods	9
5.4	Soil-structure interaction	9
5.5	Building response spectra	10
5.5.1	General requirements	10
5.5.2	Determining building response spectra based on acceleration time histories	10
6	Seismic design verification concept	11
6.1	General requirements	11
6.2	Combination of actions	11
6.3	Combinations of loads caused by directional components of a seismic event	12
6.4	Ultimate limit state (ULS)	12
6.4.1	General requirements	12
6.4.2	Ductility	13
6.4.3	Equilibrium conditions	13
6.5	Serviceability limit state (SLS)	13
6.5.1	General requirements	13
6.5.2	Deformations	14
6.6	Beyond design considerations	14
6.7	Requirements on foundations	14
7	Structure-type dependent seismic verifications	14
7.1	Structural members of reinforced and pre-stressed concrete	14
7.1.1	General requirements	14
7.1.2	Strength parameters	14
7.1.3	Verifying the load-bearing capacity	15

7.2	Steel structure parts	15
7.3	Masonry	15
7.3.1	General requirements	15
7.3.2	Verifying the load-bearing capacity	15
7.3.3	Constructional design	15
7.4	Steel composite civil structures	16
7.5	Fastening constructions	16
7.6	Buried pipelines and ducts	16
7.7	Support structures	16
Annex A (informative) Recommendations with comments		17
Annex B (informative) Simplified method for approximating building response spectra		21
Bibliography		23