

# ISO 3384-1:2024-03 (E)

## Rubber, vulcanized or thermoplastic - Determination of stress relaxation in compression - Part 1: Testing at constant temperature

---

<b>Contents</b>		<b>Page</b>
<b>Foreword</b> .....		<b>iv</b>
<b>Introduction</b> .....		<b>v</b>
<b>1 Scope</b> .....		<b>1</b>
<b>2 Normative references</b> .....		<b>1</b>
<b>3 Terms and definitions</b> .....		<b>2</b>
<b>4 Principle</b> .....		<b>2</b>
<b>5 Apparatus</b> .....		<b>2</b>
<b>6 Calibration</b> .....		<b>4</b>
<b>7 Test piece</b> .....		<b>4</b>
7.1 Type and preparation of test pieces.....		4
7.1.1 General.....		4
7.1.2 Cylindrical test pieces.....		4
7.1.3 Ring test pieces.....		4
7.2 Measurement of dimensions of test pieces.....		4
7.3 Number of test pieces.....		4
7.4 Time interval between forming and testing.....		4
7.5 Conditioning of test pieces.....		5
<b>8 Duration, temperature and test liquid</b> .....		<b>5</b>
8.1 Duration of test.....		5
8.2 Temperature of exposure.....		5
8.3 Immersion liquids.....		5
<b>9 Procedure</b> .....		<b>6</b>
9.1 Preparation.....		6
9.2 Thickness measurement.....		6
9.2.1 Cylindrical test pieces.....		6
9.2.2 Ring test pieces.....		6
9.3 Method A.....		6
9.4 Method B.....		7
<b>10 Expression of results</b> .....		<b>7</b>
<b>11 Precision</b> .....		<b>8</b>
<b>12 Test report</b> .....		<b>8</b>
<b>Annex A (informative) Precision</b> .....		<b>9</b>
<b>Annex B (informative) Calibration schedule</b> .....		<b>12</b>
<b>Bibliography</b> .....		<b>14</b>