

DIN EN ISO 11782-2:2024-10 (E)

Corrosion of metals and alloys - Corrosion fatigue testing - Part 2: Crack propagation testing using precracked specimens (ISO 11782-2:1998 + Amd 1:2024) (includes Amendment A1:2024)

Contents	Page
Foreword	4
▣ European foreword to Amendment A1 ▣	5
Foreword	6
▣ Foreword to Amendment A1 ▣	7
Introduction	8
1 Scope	9
2 Normative references	9
3 Terms and definitions	9
4 Test	11
4.1 Principle of corrosion fatigue crack propagation testing	11
4.2 Specimens for corrosion fatigue crack propagation testing	12
4.2.1 General	12
4.2.2 Specimen design	13
4.2.3 Stress intensity factor considerations	13
4.2.4 Specimen preparation	22
4.2.5 Specimen identification	22
5 Apparatus	22
5.1 Environmental chamber	22
5.2 Crack length measurement	22
6 Fatigue precracking	23
6.1 General	23
6.2 Precracking procedure	23
6.3 Precracking for low crack growth rates or ΔK_{th} determination	23
7 Test conditions	24
7.1 Environmental considerations	24
7.2 Stressing considerations	25
7.2.1 Cyclic frequency	25
7.2.2 Stress ratio	25
7.2.3 Waveform	25
7.2.4 Crack tip shielding (closure) effects	25
8 Test procedure	26
8.1 General	26
8.2 Starting procedure	26
8.3 Environmental control and monitoring	26
8.4 Determination of corrosion fatigue crack propagation rates	26
8.4.1 Length of crack	26
8.4.2 Growth rate of crack	27
8.5 Determination of corrosion fatigue threshold stress intensity factor range	28
9 Test report	28
Annex A (informative) Information on methods for measuring crack lengths	30
A.1 Visual methods	30
A.2 Electrical resistance measurement methods	30

A.2.1 DC potential drop method	30
A.2.2 AC potential drop methods	31
A.3 Compliance methods	31
Ⓜ Bibliography Ⓜ	38