

ISO 14594:2024-06 (E)

Microbeam analysis - Electron probe microanalysis - Guidelines for the determination of experimental parameters for wavelength dispersive spectroscopy

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Abbreviated terms	3
5	Experimental parameters	3
5.1	General	3
5.2	Parameters related to the electron probe	3
5.2.1	Accelerating voltage	3
5.2.2	Probe current	3
5.2.3	Magnification and field of view	3
5.3	Parameters related to wavelength dispersive X-ray spectrometers	3
5.3.1	General	3
5.3.2	Take-off angle	4
5.3.3	Wavelength resolution	4
5.3.4	X-ray detector and Pulse height analyser	4
5.3.5	Peak location (wavelength)	4
5.3.6	Background	5
5.4	Parameters related to the specimen	5
5.4.1	Specimen stage	5
5.4.2	Surface roughness	5
5.4.3	X-ray line	5
5.4.4	Analysis volume	5
6	Procedures and measurements	6
6.1	General	6
6.2	Electron probe	6
6.2.1	Probe current	6
6.2.2	Probe diameter	6
6.3	Parameters related to measured peaks	7
6.3.1	Dead time correction	7
6.3.2	Wavelength resolution of detected characteristic X-ray peaks	7
6.3.3	Background subtraction	8
6.4	Parameters related to the specimen	9
6.4.1	General	9
6.4.2	Analysis area	9
6.4.3	Analysis depth	9
6.4.4	Analysis volume	9
7	Test report	9
Annex A (informative)	Methods of estimating analysis area	11
Annex B (informative)	Methods of estimating analysis depth	13
Annex C (informative)	Method of estimating X-ray analysis volume by applying the Monte Carlo (MC) simulation	14
Bibliography		18