

ISO 7039:2024-07 (E)

Metallic materials - Tensile testing - Method for evaluating the susceptibility of materials to the effects of high-pressure gas within hollow test pieces

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Symbols	2
5	Principle	2
6	Test piece	3
6.1	General	3
6.2	Shape and dimensions	3
6.3	Inner surface of hole	3
6.4	Number of test pieces	4
7	Measurement of original cross-sectional area	4
8	Marking the original gauge length	4
9	Test equipment	4
9.1	Principle	4
9.2	Testing machine	5
9.3	Extensometer	5
9.4	Test deviation	5
10	Test conditions	5
10.1	Test gas	5
10.2	Test temperature	6
10.3	Test pressure	6
10.4	Testing rate	6
11	Evaluation of the test results	6
11.1	Yield strength, tensile strength, percentage elongation after fracture with hollow test piece	6
11.2	Percentage reduction of area at leakage	7
11.3	Relative elongation after fracture with hollow test piece, $A_h(\text{rel})$	7
11.4	Relative reduction of area at leakage with hollow test piece, $Z_h(\text{rel})$	7
11.5	Relative 0,2 % proof strength with hollow test piece, $R_{p0,2 h}(\text{rel})$	7
11.6	Relative tensile strength with hollow test piece, $R_{mh}(\text{rel})$	8
12	Test report	8
Bibliography		9