ISO 22459:2024-08 (E)

Fine ceramics (advanced ceramics, advanced technical ceramics) - Reinforcement of ceramic composites - Determination of distribution of tensile strength and tensile strain to failure of filaments within a multifilament tow at ambient temperature

Contents

Page

Foreword iv

1 Scope 1

2 Normative references 1

3 Terms and definitions 1

4 Principle 2

5 Significance and use 2

6 Apparatus 3
6.1 Tensile testing equipment 3
6.2 Data recording 4

7 Test specimen 4
7.1 General 4
7.2 Window type specimen 4
7.3 Cylindrical end type specimen 4

8 Test specimen preparation 5
8.1 General 5
8.2 Window type specimen 5
8.3 Cylindrical end type specimen 6
8.4 Number of test specimens 6

9 Test procedure 6
9.1 Determination of the initial cross-section area 6
9.2 Determination of the gauge length 6
9.3 Gripping 6
9.4 Selection of strain rate 7
9.5 Test procedure 7
9.6 Determination of load train compliance 7
9.7 Test validity 8

10 Calculation of results 8
10.1 Calculation of the load train compliance Cl 8
10.2 Calculation of probability of filament rupture Pj from the tests on specimens with a gauge length of 200 mm 10
10.2.1 Determination of the true origin 10
10.2.2 Construction of envelope curve and determination of instantaneous compliance Ct,j 10
10.2.3 Probability of filament rupture 11
10.3 Distribution of filament rupture strain 11
10.3.1 Calculation of filament rupture strain 11
10.3.2 Filament rupture strain distribution 11
10.4 Distribution of filament strength 12
10.4.1 Initial cross-section area 12
10.4.2 Calculation of filament strength 12

10.4.3 Filament strength distribution 13
10.4.4 Average filament strengths 13
10.4.5 Mean filament strength 14

11 Test report 14

Annex A (informative) Abstract of the handbook of mathematical functions 15

Bibliography 16