

# ISO 21561-2:2024-08 (E)

## Styrene-butadiene rubber (SBR) - Determination of the microstructure of solution-polymerized SBR - Part 2: Fourier transform infrared spectrometry (FTIR) with attenuated total reflection (ATR) method

---

<b>Contents</b>	<b>Page</b>
Foreword .....	iv
1 Scope .....	1
2 Normative references .....	1
3 Terms and definitions .....	1
4 Principle .....	2
5 Apparatus .....	2
6 Calibration .....	2
6.1 FTIR .....	2
6.2 ATR .....	2
7 Sampling .....	2
8 Procedure for measuring ATR spectrum .....	3
9 Determination of the microstructure of butadiene and the styrene content .....	3
9.1 Measurement of the absorbance for each microstructure component .....	3
9.2 Calculation of microstructures .....	4
9.2.1 General .....	4
9.2.2 Base line correction of each absorbance peak .....	4
9.2.3 Ratio of absorbance .....	5
9.2.4 Second order terms .....	5
9.2.5 Styrene content and contents of three microstructure types of butadiene portion by regression formulae .....	5
9.2.6 of three microstructure types relative to butadiene portion in the S-SBR .....	6
10 Precision .....	6
11 Test report .....	6
Annex A (informative) Precision results from an interlaboratory test programme .....	7
Annex B (informative) Acquisition of regression formulae for microstructure .....	10
Annex C (informative) Determination of microstructure by NMR spectrometry .....	12
Bibliography .....	15