

ISO 9812:2024-10 (E)

Corrosion of metals and alloys - Corrosion test method for disinfectant - Spray test method

Contents

Page

| | |
|---|----------|
| Foreword..... | iv |
| Introduction..... | v |
| 1 Scope..... | 1 |
| 2 Normative references..... | 1 |
| 3 Terms and definitions..... | 1 |
| 4 Apparatus..... | 2 |
| 4.1 Test cabinet..... | 2 |
| 4.2 Spray equipment..... | 2 |
| 4.3 Specimen supporting device..... | 2 |
| 4.4 Oven..... | 2 |
| 4.5 Analytical balance..... | 2 |
| 4.6 Vernier caliper..... | 3 |
| 5 Reagents and materials..... | 3 |
| 5.1 Experimental water..... | 3 |
| 5.2 Acetone..... | 3 |
| 5.3 Ethanol..... | 3 |
| 5.4 Abrasive paper..... | 3 |
| 6 Test specimens..... | 3 |
| 7 Pretreatment of test specimens..... | 3 |
| 8 Arrangement of the test specimens..... | 3 |
| 9 Operation condition..... | 4 |
| 9.1 Test environment..... | 4 |
| 9.2 Disinfectant solution concentration and the disinfectant solution usage..... | 4 |
| 9.3 Temperature..... | 4 |
| 9.4 Duration of the test..... | 4 |
| 10 Procedure..... | 5 |
| 11 Calculation of the corrosion rate..... | 6 |
| 12 Report..... | 6 |
| Annex A (normative) Result of corrosion test..... | 7 |
| Annex B (informative) Schematic diagram of test cabinet associated apparatus for disinfectant corrosion test in the spray condition..... | 8 |