

DIN EN ISO 16811:2025-06 (E)

Non-destructive testing - Ultrasonic testing - Sensitivity and range setting (ISO 16811:2025)

Contents

| | Page |
|---|-----------|
| Foreword..... | v |
| Introduction..... | vi |
| 1 Scope..... | 1 |
| 2 Normative references..... | 1 |
| 3 Terms and definitions..... | 1 |
| 4 Quantities and symbols..... | 1 |
| 5 Qualification of personnel..... | 3 |
| 6 Test equipment..... | 3 |
| 6.1 Instrument..... | 3 |
| 6.2 Probes..... | 3 |
| 6.2.1 General..... | 3 |
| 6.2.2 Probe selection..... | 3 |
| 6.2.3 Frequency and dimensions of transducer..... | 4 |
| 6.2.4 Dead zone..... | 4 |
| 6.2.5 Damping..... | 4 |
| 6.2.6 Focusing probes..... | 4 |
| 6.3 Coupling media..... | 4 |
| 6.4 Standard blocks..... | 5 |
| 6.5 Reference blocks..... | 5 |
| 6.6 Specific test blocks..... | 6 |
| 7 Categories of test objects..... | 6 |
| 8 Test objects, reference blocks and reference reflectors..... | 6 |
| 9 Probes..... | 9 |
| 9.1 General..... | 9 |
| 9.2 Longitudinally curved probes..... | 10 |
| 9.2.1 Convex scanning surface..... | 10 |
| 9.2.2 Concave scanning surface..... | 10 |
| 9.3 Transversely curved probes..... | 10 |
| 9.3.1 Convex scanning surface..... | 10 |
| 9.3.2 Concave scanning surface..... | 11 |
| 10 Determination of probe index point and beam angle..... | 11 |
| 10.1 General..... | 11 |
| 10.2 Flat angle-beam probes..... | 11 |
| 10.2.1 Calibration block technique..... | 11 |
| 10.2.2 Reference block technique..... | 11 |
| 10.3 Angle-beam probes curved longitudinally..... | 11 |
| 10.3.1 Mechanical determination..... | 11 |
| 10.3.2 Reference block technique..... | 13 |
| 10.4 Angle-beam probes curved transversely..... | 13 |
| 10.4.1 Mechanical determination..... | 13 |
| 10.4.2 Reference block technique..... | 14 |
| 10.5 Probes curved in two directions..... | 15 |
| 10.6 Probes for use on materials other than non-alloy steel..... | 15 |
| 11 Time base setting..... | 15 |
| 11.1 General..... | 15 |

| | | |
|------------------------------|--|-----------|
| 11.2 | Reference blocks and reference reflectors..... | 16 |
| 11.3 | Straight-beam probes..... | 16 |
| 11.3.1 | Single-reflector technique..... | 16 |
| 11.3.2 | Multiple-reflector technique..... | 16 |
| 11.4 | Angle-beam probes..... | 17 |
| 11.4.1 | Radius technique..... | 17 |
| 11.4.2 | Straight-beam probe technique..... | 17 |
| 11.4.3 | Reference block technique..... | 17 |
| 11.4.4 | Contoured probes..... | 17 |
| 11.5 | Alternative range settings for angle-beam probes..... | 17 |
| 11.5.1 | Flat surfaces..... | 17 |
| 11.5.2 | Curved surfaces..... | 18 |
| 12 | Sensitivity setting and echo height evaluation..... | 19 |
| 12.1 | General..... | 19 |
| 12.2 | Angle of incidence..... | 20 |
| 12.3 | Distance-amplitude curve (DAC) technique..... | 20 |
| 12.3.1 | Reference blocks..... | 20 |
| 12.3.2 | Preparation of a distance-amplitude curve..... | 21 |
| 12.3.3 | Evaluation of signals using a distance-amplitude curve..... | 22 |
| 12.3.4 | Evaluation of signals using a reference height..... | 22 |
| 12.4 | Distance-gain-size (DGS) technique..... | 23 |
| 12.4.1 | General..... | 23 |
| 12.4.2 | Reference blocks..... | 25 |
| 12.4.3 | Use of DGS diagrams..... | 26 |
| 12.4.4 | Restrictions on use of the DGS technique due to geometry..... | 28 |
| 12.5 | Transfer correction..... | 28 |
| 12.5.1 | General..... | 28 |
| 12.5.2 | Fixed path length technique..... | 29 |
| 12.5.3 | Comparative technique..... | 29 |
| 12.5.4 | Compensation for local variations in transfer correction..... | 30 |
| Annex A (informative) | Determination of sound path distance and angle of incidence in category | |
| | 2 test objects..... | 31 |
| Annex B (informative) | General DGS diagram..... | 36 |
| Annex C (informative) | Determination of contact transfer correction factors..... | 38 |
| Bibliography..... | | 41 |