

DIN EN ISO 16827:2025-09 (E)

Non-destructive testing - Ultrasonic testing - Characterization and sizing of discontinuities (ISO 16827:2025)

Contents

	Page
Foreword.....	iv
Introduction.....	v
1 Scope.....	1
2 Normative references.....	1
3 Terms and definitions.....	1
4 Principles of characterization of discontinuities.....	1
4.1 General.....	1
4.2 Requirements for surface condition.....	2
5 Pulse-echo techniques.....	2
5.1 General.....	2
5.2 Location of discontinuity.....	2
5.3 Orientation of discontinuity.....	3
5.4 Assessment of multiple indications.....	3
5.5 Shape of discontinuity.....	4
5.5.1 Simple classification.....	4
5.5.2 Detailed classification.....	4
5.6 Maximum echo height of indication.....	5
5.7 Size of discontinuity.....	5
5.7.1 General.....	5
5.7.2 Maximum echo height techniques.....	5
5.7.3 Probe movement sizing techniques.....	6
5.7.4 Selection of sizing techniques.....	7
5.7.5 Sizing techniques with focusing probes.....	8
5.7.6 Use of mathematical algorithms for sizing.....	8
5.7.7 Special sizing techniques.....	8
6 Through-transmission technique.....	9
6.1 General.....	9
6.2 Location of discontinuity.....	9
6.3 Evaluation of multiple discontinuities.....	9
6.4 Reduction of signal amplitude.....	10
6.5 Size of discontinuity.....	10
Annex A (normative) Analysis of multiple indications.....	12
Annex B (normative) Techniques for the classification of discontinuity shape.....	14
Annex C (normative) Sizing technique using the maximum echo height.....	23
Annex D (normative) Sizing techniques using probe movement.....	25
Annex E (informative) Iterative sizing technique.....	37
Annex F (informative) Mathematical algorithms for the estimation of the actual size of a discontinuity.....	41
Annex G (informative) Examples of special sizing techniques.....	47
Bibliography.....	50