

# ISO 2478:2025-09 (E)

## Dense shaped refractory products - Determination of permanent change in dimensions on heating

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Principle .....</b>	<b>2</b>
<b>5</b>	<b>Apparatus .....</b>	<b>2</b>
<b>6</b>	<b>Test pieces .....</b>	<b>4</b>
<b>6.1</b>	<b>Number of test pieces .....</b>	<b>4</b>
<b>6.2</b>	<b>Preparation of test pieces .....</b>	<b>4</b>
<b>7</b>	<b>Procedure .....</b>	<b>5</b>
<b>7.1</b>	<b>Drying of the test pieces .....</b>	<b>5</b>
<b>7.2</b>	<b>Measurement of the test pieces .....</b>	<b>5</b>
<b>7.2.1</b>	<b>Linear measurement by dial gauge apparatus (Method 1A) .....</b>	<b>5</b>
<b>7.2.2</b>	<b>Linear measurement by Vernier callipers (Method 1B) .....</b>	<b>5</b>
<b>7.2.3</b>	<b>Volume measurement (Method 2) .....</b>	<b>6</b>
<b>7.3</b>	<b>Mounting of test pieces in the furnace .....</b>	<b>6</b>
<b>7.4</b>	<b>Test temperature .....</b>	<b>6</b>
<b>7.5</b>	<b>Temperature measurement and distribution .....</b>	<b>6</b>
<b>7.6</b>	<b>Heating .....</b>	<b>7</b>
<b>7.7</b>	<b>Maintenance of test temperature .....</b>	<b>7</b>
<b>7.8</b>	<b>Sampling of furnace atmosphere .....</b>	<b>7</b>
<b>7.9</b>	<b>Cooling .....</b>	<b>7</b>
<b>7.10</b>	<b>Measurement of test pieces after firing .....</b>	<b>7</b>
<b>7.10.1</b>	<b>Linear measurement (Methods 1A and 1B) .....</b>	<b>7</b>
<b>7.10.2</b>	<b>Volume measurement (Method 2) .....</b>	<b>8</b>
<b>8</b>	<b>Expression of results .....</b>	<b>8</b>
<b>9</b>	<b>Test report .....</b>	<b>8</b>
<b>Annex A (informative)</b>	<b>Precision and bias .....</b>	<b>9</b>
<b>Bibliography .....</b>		<b>10</b>