DIN EN 1427:2026-07 (E)

Bitumens and bituminous binders - Determination of the softening point - Ring and Ball method

Contents

Page

European foreword 4

1 Scope 7

2 Normative references 7

3 Terms and definitions 7

4 Principle 7

5 Reagents and materials 7

6 Apparatus 8
6.1 Ring and Ball apparatus 8
6.2 Calibration and verification 10

7 Test sample preparation 10

8 Procedure and reporting 11
8.1 General 11
8.2 Selection of bath liquid and temperature measuring device 11
8.2.1 Initial selection 11
8.2.2 Assessment of correct selection of bath liquid 11
8.3 Procedure for softening points 80 °C 12
8.4 Procedure for softening points above 80 °C and up to 150 °C 13

9 Expression of results 14

10 Precision 14
10.1 General 14
10.2 Repeatability 14
10.3 Reproducibility 14

11 Test report 15

12 Figures 16

Annex A (informative) Determination or verification of the response time of the temperature measuring device 21

A.1 General 21
A.2 Context 21
A.3 Principle 21
A.4 Procedure 24
A.4.1 General 24
A.4.2 Procedure 24

Annex B (informative) Examples of valid and invalid temperature gradients 25

B.1 General 25
B.2 Example 1 Bath liquid: Water 26

B.3 Example 2 Bath liquid: Glycerol 27

Annex C (informative) Examples of even temperature distribution and experiences on beaker - stirrer combinations 29

C.1 Uneven temperature distribution due to layering of glycerol 29
C.2 Examples of beaker - stirrer combinations 29

Annex D (informative) Trials on silicone oil as alternative to glycerol as bath liquid 31

D.1 General 31
D.2 Verification of influence of silicone oil on the test sample 31
D.3 Verification of speed of stirring on test results 31

Bibliography 33