ISO 13935-2:2026-04 (E)

Textiles - Seam tensile properties of fabrics and made-up textile articles - Part 2: Determination of maximum force to seam rupture using the grab method

Contents

Page

Foreword ... iv

Introduction ... v

1 Scope ... 1

2 Normative references ... 1

3 Terms and definitions ... 1

4 Principle ... 2

5 Sampling ... 2

6 Apparatus ... 3

6.1 CRE machine ... 3

6.2 Equipment for sewing defined seams ... 4

6.3 Equipment for cutting test specimens ... 4

7 Atmosphere for conditioning and testing ... 4

8 Preparation of seams and of test specimens ... 4

8.1 Preparation of seams, if required, before testing ... 4

8.2 Preparation of adjacent test specimens from one laboratory sample ... 4

8.3 Preparation of test specimens ... 5

9 Procedure ... 7

9.1 Gauge length ... 7

9.2 Rate of extension ... 7

9.3 Mounting of test specimens ... 7

9.4 Operation ... 7

10 Calculation and expression of results ... 7

11 Test report ... 8

Annex A (informative) **Arrangements of jaws for the grab test** ... 9

Annex B (informative) **Considerations on straight seams and sampling of structural seams on garments** ... 10

Bibliography ... 13