

ISO 6940:2026-05 (E)

Textile fabrics - Burning behaviour - Determination of ease of ignition of vertically oriented specimens

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Principle	1
5	Apparatus	2
5.6	Timing devices	2
6	Cautionary measure	4
6.1	Construction of testing equipment	4
6.2	Location of test apparatus	4
6.3	Health and safety of test operators	4
7	Sampling	5
7.1	Number of test specimens	5
7.2	Test specimen holder pin location marks	5
7.3	Test specimen size	5
8	Conditioning and testing atmosphere	5
8.1	Conditioning	5
8.2	Testing atmosphere	5
9	Setting up the apparatus	6
9.1	Procedure A (Surface ignition)	6
9.1.1	Mounting of the test specimen	6
9.1.2	Operating position of the burner	6
9.1.3	Flame adjustment -- Horizontal reach	6
9.1.4	Flame position	6
9.2	Procedure B (Bottom edge ignition)	6
9.2.1	Mounting of the test specimen	6
9.2.2	Operating position of the burner	6
9.2.3	Flame adjustment -- vertical flame height	7
9.2.4	Flame position	7
10	Test procedure	8
10.1	Surface ignition	8
10.2	Bottom edge ignition	9
11	Calculation of the mean ignition time	10
12	Precision	10
13	Test report	10

Annex A (normative) Description and construction of the burner	12
Annex B (informative) Calculation of mean ignition time -- Work example	13
Annex C (informative) Experimental techniques	14
Bibliography	15