

ISO 24046:2026-08 (E)

Fine ceramics (advanced ceramics, advanced technical ceramics) - Methods of test for reinforcements - Determination of the tensile properties of resin-impregnated yarns

Contents	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Principle	3
5 Apparatus and material	3
5.1 Resin	3
5.2 Impregnation apparatus	3
5.3 Curing oven with temperature control	4
5.4 Tensile-testing machine and extensometer	4
5.4.1 Tensile-testing machine	4
5.4.2 Extensometer	4
5.5 Balance	4
5.6 Ruler	4
6 Test specimens	4
6.1 Number of test specimens	4
6.2 Impregnation of test specimens	4
6.3 Determination of other fibre properties	5
6.3.1 General	5
6.3.2 Linear density of the yarn	5
6.3.3 Size content of the yarn	5
6.3.4 Density of the ceramic fibre	5
6.4 Criteria for selection of the test specimens	5
6.4.1 Specimens	5
6.4.2 Resin content of the specimens	5
6.4.3 Impregnated yarn	6
7 Atmospheres for conditioning and testing	6
8 Procedure for tensile testing	6
8.1 Procedure	6
8.2 Determination of load train compliance	6
8.3 Test validity	6
9 Calculation of results	7
9.1 Tensile strength	7
9.2 Calculation of the load train compliance	7
9.3 Calculation of instantaneous total compliance and longitudinal deformation of resin-impregnated yarn	8
9.4 Tensile modulus of elasticity	9
9.5 Tensile strain at maximum force (percentage elongation at failure)	10

9.5.1	Calculation method (1)	10
9.5.2	Calculation method (2)	11
10	Statistics	11
11	Test report	11
Annex A (informative) Examples of heat-curable epoxy-resin systems		13
Annex B (informative) Examples of resin-impregnating apparatus		14
Annex C (informative) Example of extensometer		15
Bibliography		17