ISO 24046:2026-08 (E)

Fine ceramics (advanced ceramics, advanced technical ceramics) - Methods of test for reinforcements - Determination of the tensile properties of resin-impregnated yarns

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Terms and definitions 1

4 Principle 3

5 Apparatus and material 3
5.1 Resin 3
5.2 Impregnation apparatus 3
5.3 Curing oven with temperature control 4
5.4 Tensile-testing machine and extensometer 4
5.4.1 Tensile-testing machine 4
5.4.2 Extensometer 4
5.5 Balance 4
5.6 Ruler 4

6 Test specimens 4
6.1 Number of test specimens 4
6.2 Impregnation of test specimens 4
6.3 Determination of other fibre properties 5
6.3.1 General 5
6.3.2 Linear density of the yarn 5
6.3.3 Size content of the yarn 5
6.3.4 Density of the ceramic fibre 5
6.4 Criteria for selection of the test specimens 5
6.4.1 Specimens 5
6.4.2 Resin content of the specimens 5
6.4.3 Impregnated yarn 6

7 Atmospheres for conditioning and testing 6

8 Procedure for tensile testing 6
8.1 Procedure 6
8.2 Determination of load train compliance 6
8.3 Test validity 6

9 Calculation of results 7
9.1 Tensile strength 7
9.2 Calculation of the load train compliance 7
9.3 Calculation of instantaneous total compliance and longitudinal deformation of resin-impregnated yarn 8
9.4 Tensile modulus of elasticity 9
9.5 Tensile strain at maximum force (percentage elongation at failure) 10

9.5.1 Calculation method (1) 10
9.5.2 Calculation method (2) 11

10 Statistics 11

11 Test report 11

Annex A (informative) Examples of heat-curable epoxy-resin systems 13

Annex B (informative) Examples of resin-impregnating apparatus 14

Annex C (informative) Example of extensometer 15

Bibliography 17