

# ISO 12917-2:2002-09 (E)

## Petroleum and liquid petroleum products - Calibration of horizontal cylindrical tanks - Part 2: Internal electro-optical distance-ranging method

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>2</b>
<b>4</b>	<b>Precautions .....</b>	<b>2</b>
<b>5</b>	<b>Equipment .....</b>	<b>2</b>
<b>5.1</b>	<b>Electro-optical distance-ranging instrument .....</b>	<b>2</b>
<b>5.2</b>	<b>Instrument mounting .....</b>	<b>2</b>
<b>5.3</b>	<b>Laser-beam emitter .....</b>	<b>2</b>
<b>5.4</b>	<b>Stadia .....</b>	<b>3</b>
<b>5.5</b>	<b>Auxiliary equipment .....</b>	<b>3</b>
<b>6</b>	<b>General considerations .....</b>	<b>3</b>
<b>7</b>	<b>EODR instrument set up within the tank .....</b>	<b>3</b>
<b>8</b>	<b>Selection of target points .....</b>	<b>4</b>
<b>8.1</b>	<b>Introduction .....</b>	<b>4</b>
<b>8.2</b>	<b>Location of target points -- General principle .....</b>	<b>5</b>
<b>8.3</b>	<b>Cylindrical courses .....</b>	<b>5</b>
<b>8.4</b>	<b>Heads .....</b>	<b>5</b>
<b>9</b>	<b>Procedure for calibration .....</b>	<b>5</b>
<b>10</b>	<b>Tolerances of reference target points .....</b>	<b>5</b>
<b>10.1</b>	<b>Distance verification .....</b>	<b>5</b>
<b>10.2</b>	<b>Verification of horizontal and vertical angles .....</b>	<b>6</b>
<b>11</b>	<b>Additional measurements .....</b>	<b>6</b>
<b>11.1</b>	<b>Reference-height determination and reference-point position .....</b>	<b>6</b>
<b>11.2</b>	<b>Data .....</b>	<b>7</b>
<b>11.3</b>	<b>Drawings .....</b>	<b>7</b>
<b>12</b>	<b>Calculation and development of capacity tables .....</b>	<b>7</b>
<b>Annex A (normative) Determination of the limiting angle of incidence .....</b>		<b>8</b>
<b>Annex B (informative) Numerical example .....</b>		<b>9</b>