

# ISO 20864:2004-12 (E)

## Footwear — Test methods for stiffeners and toepuffs — Mechanical characteristics

---

<b>Contents</b>		<b>page</b>
<b>Foreword</b> .....		<b>v</b>
<b>1</b> <b>Scope</b> .....		<b>1</b>
<b>2</b> <b>Normative references</b> .....		<b>1</b>
<b>3</b> <b>Terms and definitions</b> .....		<b>1</b>
<b>4</b> <b>Apparatus and material</b> .....		<b>1</b>
<b>4.1</b> <b>General</b> .....		<b>1</b>
<b>4.2</b> <b>Methods 1 and 2</b> .....		<b>1</b>
<b>4.3</b> <b>Method 1 (only)</b> .....		<b>4</b>
<b>4.4</b> <b>Method 2 (only)</b> .....		<b>4</b>
<b>4.5</b> <b>Method 3</b> .....		<b>4</b>
<b>4.6</b> <b>All methods</b> .....		<b>5</b>
<b>5</b> <b>Sampling and conditioning</b> .....		<b>9</b>
<b>5.1</b> <b>Method 1</b> .....		<b>9</b>
<b>5.2</b> <b>Method 2</b> .....		<b>10</b>
<b>5.3</b> <b>Method 3</b> .....		<b>11</b>
<b>6</b> <b>Procedure (all methods)</b> .....		<b>12</b>
<b>6.1</b> <b>Shape retention value</b> .....		<b>12</b>
<b>6.1.1</b> <b>Dry testing</b> .....		<b>12</b>
<b>6.1.2</b> <b>Wet testing</b> .....		<b>12</b>
<b>6.2</b> <b>Collapsing load of the test specimen</b> .....		<b>12</b>
<b>6.2.1</b> <b>Dry testing</b> .....		<b>12</b>
<b>6.2.2</b> <b>Wet testing</b> .....		<b>13</b>
<b>6.3</b> <b>Shape retention after ten collapses</b> .....		<b>13</b>
<b>6.3.1</b> <b>Dry testing</b> .....		<b>13</b>
<b>6.3.2</b> <b>Wet testing</b> .....		<b>13</b>
<b>7</b> <b>Expression of results</b> .....		<b>13</b>
<b>7.1</b> <b>Shape retention</b> .....		<b>13</b>
<b>7.2</b> <b>Collapsing load</b> .....		<b>14</b>
<b>7.3</b> <b>Shape retention after ten collapses</b> .....		<b>14</b>
<b>7.4</b> <b>Resilience</b> .....		<b>14</b>
<b>7.5</b> <b>Moisture resistance</b> .....		<b>14</b>
<b>8</b> <b>Test report</b> .....		<b>14</b>
<b>Annex ZA</b> (normative) <b>Normative references to International publications with their corresponding European publications</b> .....		<b>15</b>
<b>Bibliography</b> .....		<b>16</b>