ISO 17874-2:2004-12 (E)

Remote-handling devices for radioactive materials - Part 2: Mechanical master-slave manipulators

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Terms and definitions 1

4 General architecture and classification 3
4.1 General architecture 3
4.2 Classification 4
4.3 Kinematics 7

5 Basic considerations for the choice of a manipulator 9
5.1 General criteria 9
5.2 Particular criteria 10
5.3 Mounting of the master-slave manipulators 12
5.4 Leak-tightness and protection against contamination 13

6 Different manipulator mounting methods and associated requirements 15
6.1 Unsealed connection tube, with a gaiter 15
6.2 Unsealed connection tube, without gaiter 21
6.3 Sealed connection tube 21
6.4 Design of the lower end of the gaiters 22
6.5 Special case of double gaiters 25
6.6 Replacement of manipulator gaiters 26
6.7 Attachment of leak-tight manipulator gaiters 29

7 Accessories 29
7.1 Connection tubes with shielding 29
7.2 Balancing 29
7.3 Terminations 30
7.4 Electricity supply 31
7.5 Various 31

Annex A (normative) Method of measurement of no-load forces and torques, flexures and backlashes 33

Annex B (informative) Typical disconnection stations 45

Bibliography 48