

ISO 17874-2:2004-12 (E)

Remote-handling devices for radioactive materials - Part 2: Mechanical master-slave manipulators

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	General architecture and classification	3
4.1	General architecture	3
4.2	Classification	4
4.3	Kinematics	7
5	Basic considerations for the choice of a manipulator	9
5.1	General criteria	9
5.2	Particular criteria	10
5.3	Mounting of the master-slave manipulators	12
5.4	Leak-tightness and protection against contamination	13
6	Different manipulator mounting methods and associated requirements	15
6.1	Unsealed connection tube, with a gaiter	15
6.2	Unsealed connection tube, without gaiter	21
6.3	Sealed connection tube	21
6.4	Design of the lower end of the gaiters	22
6.5	Special case of double gaiters	25
6.6	Replacement of manipulator gaiters	26
6.7	Attachment of leak-tight manipulator gaiters	29
7	Accessories	29
7.1	Connection tubes with shielding	29
7.2	Balancing	29
7.3	Terminations	30
7.4	Electricity supply	31
7.5	Various	31
Annex A (normative)	Method of measurement of no-load forces and torques, flexures and backlashes	33
Annex B (informative)	Typical disconnection stations	45
Bibliography		48