

# ISO 12183:2005-02 (E)

## Nuclear fuel technology - Controlled-potential coulometric assay of plutonium

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Principle .....</b>	<b>1</b>
<b>4</b>	<b>Reagents .....</b>	<b>2</b>
<b>5</b>	<b>Apparatus .....</b>	<b>2</b>
<b>6</b>	<b>Procedure .....</b>	<b>7</b>
<b>6.1</b>	<b>Plutonium determination .....</b>	<b>7</b>
<b>6.2</b>	<b>Analysis of subsequent samples .....</b>	<b>12</b>
<b>7</b>	<b>Expression of results .....</b>	<b>12</b>
<b>7.1</b>	<b>Calculation of the electrical calibration factor .....</b>	<b>12</b>
<b>7.2</b>	<b>Calculation of the blank .....</b>	<b>12</b>
<b>7.3</b>	<b>Fraction of electrolysed plutonium .....</b>	<b>13</b>
<b>7.4</b>	<b>Plutonium content .....</b>	<b>14</b>
<b>7.5</b>	<b>Quality control .....</b>	<b>14</b>
<b>8</b>	<b>Characteristics of the method .....</b>	<b>14</b>
<b>8.1</b>	<b>Repeatability .....</b>	<b>14</b>
<b>8.2</b>	<b>Confidence interval .....</b>	<b>14</b>
<b>8.3</b>	<b>Analysis time .....</b>	<b>15</b>
<b>9</b>	<b>Interferences .....</b>	<b>15</b>
<b>10</b>	<b>Procedure variations and optimisation .....</b>	<b>17</b>
<b>10.1</b>	<b>Accountability measurements .....</b>	<b>17</b>
<b>10.2</b>	<b>Process control measurements .....</b>	<b>18</b>
<b>10.3</b>	<b>Measurement cell design .....</b>	<b>18</b>
<b>10.4</b>	<b>Electrolyte and electrode options .....</b>	<b>18</b>
<b>10.5</b>	<b>Test sample size .....</b>	<b>19</b>
<b>10.6</b>	<b>Background current corrections .....</b>	<b>19</b>
<b>10.7</b>	<b>Correction for iron .....</b>	<b>19</b>
<b>10.8</b>	<b>Control-potential adjustment .....</b>	<b>20</b>
<b>Annex A (normative) Purification by anion-exchange separation .....</b>		<b>21</b>
<b>Annex B (normative) Determination of Formal Potential E<sub>0</sub> .....</b>		<b>23</b>
<b>Bibliography .....</b>		<b>24</b>