

DIN 51309:2005-12 (E)

Materials testing machines - Calibration of static torque measuring devices

Contents		Page
Foreword		4
1	Scope	5
2	Normative references	5
3	Symbols	5
4	Characteristics of the torque measuring instrument	7
4.1	Description and marking of the torque measuring instrument	7
4.2	Inducing the torque	7
4.3	Measurement of the torque by deformation	7
5	Calibration of the torque measuring instrument	7
5.1	General	7
5.1.1	Requirements	7
5.1.2	Overload check	8
5.2	Resolution of the display unit	8
5.2.1	Scale indication	8
5.2.2	Numeric display	8
5.2.3	Indication fluctuation	8
5.2.4	Units	8
5.2.5	Measurement range initial value	8
5.3	Preparation of the calibration	8
5.3.1	Display unit	8
5.3.2	Temperature equalization	9
5.3.3	Transducer zero value I_s	9
5.3.4	Installation direction, transducer connection	9
5.4	Carrying out the calibration	9
5.4.1	Scope of the calibration and procedure	9
5.4.2	Preloading	10
5.4.3	Installation position	10
5.4.4	Carrying out the calibration	10
5.4.5	Loading conditions	11
5.4.6	Displayed value corrected for the zero value $X_j(MK)$	11
5.4.7	Evaluation of the torque measuring instruments	11
5.4.8	Short-time creeping	14
6	Classification of the torque measuring instrument	14
6.1	Classification principle	14
6.2	Measurement range initial value and classification criteria	14
6.2.1	Measurement range initial value	14
6.2.2	Classification criteria	14
6.3	Calibration certificate and recalibration	15
6.3.1	Calibration certificate	15
6.3.2	Recalibration	16
7	Standard designation	16
Annex A (normative)	Application of calibrated torque measuring instruments	17

Annex B (informative) Recommended dimensions for torque transducers, including couplings for their adaptation in torque calibrators	18
Annex C (informative) Determination of the relative expanded measurement uncertainty W for the calibration of torque measuring instruments	19
C.1 Determination of the measurement uncertainty of the interpolated calibration result for the calibration of torque measuring instruments	19
C.1.1 Model	19
C.1.2 Measurement uncertainty budget	20
Annex D (informative) Calibration procedure	24
Annex E (informative) Features for measurement of vibratory torque	25
Bibliography	27
List of figures Figure B.1	18
Figure D.1 -- Example of the preloadings and measurement series for the classes 0,05 and 0,1	24
Figure D.2 -- Example of the preloadings and measurement series of square drive transducers for the classes 0,2 and 0,5	24
Figure D.3 -- Example of the preloadings and measurement series of square drive transducers for the classes 1 to 5	24
Figure E.1 -- Interpolation deviations for clockwise and anti-clockwise torque, related to the corresponding zero points (here and in the following, filled symbols signify: increasing value of the torque; blank symbols: decreasing value)	25
Figure E.2 -- Interpolation deviations for alternating torque with integrated contours for clockwise and anti-clockwise torque, related to the mean value of the associated zero points	26
Figure E.3 -- Range of the interpolation deviation (thick line) for an alternating torque transducer with unknown history	26
List of tables Table 1 -- Symbols, units and designation	5
Table 2 -- Number of series of measurements required	10
Table 3 -- Classification characteristics of the torque measuring instruments	15
Table B.1	18
Table C.1 -- Distribution functions for the calculation of the relative standard deviations for the parameters calculated from the ranges determined from experiment	20
Table C.2 -- Example for the tabular calculation of the relative standard measurement uncertainty w for torque measuring instruments for static torques	23