

# ISO 1817:2005-10 (E)

## Rubber, vulcanized - Determination of the effect of liquids

---

<b>Contents</b>		<b>Page</b>
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Apparatus .....</b>	<b>2</b>
<b>4</b>	<b>Test liquids .....</b>	<b>3</b>
<b>5</b>	<b>Test pieces .....</b>	<b>4</b>
<b>5.1</b>	<b>Preparation .....</b>	<b>4</b>
<b>5.2</b>	<b>Dimensions .....</b>	<b>4</b>
<b>5.3</b>	<b>Time interval between vulcanization and testing .....</b>	<b>4</b>
<b>5.4</b>	<b>Conditioning .....</b>	<b>4</b>
<b>6</b>	<b>Immersion in the test liquid .....</b>	<b>5</b>
<b>6.1</b>	<b>Temperature .....</b>	<b>5</b>
<b>6.2</b>	<b>Duration .....</b>	<b>5</b>
<b>7</b>	<b>Procedure .....</b>	<b>5</b>
<b>7.1</b>	<b>General .....</b>	<b>5</b>
<b>7.2</b>	<b>Change in mass .....</b>	<b>6</b>
<b>7.3</b>	<b>Change in volume .....</b>	<b>6</b>
<b>7.4</b>	<b>Change in dimensions .....</b>	<b>7</b>
<b>7.5</b>	<b>Change in surface area .....</b>	<b>8</b>
<b>7.6</b>	<b>Change in hardness .....</b>	<b>8</b>
<b>7.7</b>	<b>Change in tensile stress-strain properties .....</b>	<b>9</b>
<b>7.8</b>	<b>Testing with liquid on one surface only .....</b>	<b>9</b>
<b>7.9</b>	<b>Determination of extractable matter .....</b>	<b>10</b>
<b>8</b>	<b>Test report .....</b>	<b>10</b>
<b>Annex A (normative) Reference liquids .....</b>		<b>12</b>
<b>A.1</b>	<b>Standard simulated fuels .....</b>	<b>12</b>
<b>A.2</b>	<b>Reference oils .....</b>	<b>13</b>
<b>A.3</b>	<b>Simulated service liquids .....</b>	<b>15</b>
<b>A.4</b>	<b>Chemical reagents .....</b>	<b>15</b>