

DIN EN 15317:2007-05 (E nglisch)

Non-destructive testing - Ultrasonic testing - Characterization and verification of ultrasonic thickness measuring equipment

Contents		Page
Foreword		4
1	Scope	5
2	Normative references	5
3	Terms and definitions	5
4	General requirements for compliance	5
5	Manufacturer's technical specification for ultrasonic thickness measuring equipment	6
5.1	General	6
5.2	General attributes	6
5.3	Display	6
5.4	Transmitter	7
5.5	Receiver	7
5.6	Other information	7
6	Calibration blocks	7
6.1	General	7
6.2	Material	7
6.3	Shape and size	8
7	Performance requirements for ultrasonic thickness measuring equipment	9
8	Probes	10
9	Group 1 tests	11
9.1	General	11
9.2	Equipment required for Group 1 tests	11
9.3	Stability against temperature	11
9.4	Low battery warning	11
9.5	Battery operational time	12
9.6	Operational voltage range	12
9.7	Operational current range	12
9.8	Operational temperature range	13
9.9	Pulse repetition frequency, PRF	13
9.10	Transmitter pulse shape, rise-time and peak voltage	13
9.11	Receiver frequency range of operation	15
9.12	Minimum and maximum measurable thicknesses	15
9.13	Accuracy and resolution	15
9.14	Range of velocity setting (calibration)	15
9.15	Calibration mechanisms	15
9.16	Calibration setting storage	16
9.17	Data storage	16
9.18	Printing	16
9.19	Display and recall	17
9.20	Display response time	17
10	Group 2 tests	17
10.1	General	17

10.2	Equipment required for Group 2 tests	17
10.3	General characteristics	18
10.4	General mechanical state and external aspects	18
11	Group 3 tests	18
11.1	General	18
11.2	General mechanical state and external aspects	18
11.3	Calibration mechanisms	18
11.4	Calibration setting storage	18
11.5	Data storage	19