

ISO 3452-2:2006-08 (E)

Non-destructive testing - Penetrant testing - Part 2: Testing of penetrant materials

| Contents | | Page |
|---|--|-------------|
| Foreword | | iv |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Classification | 2 |
| 4.1 | Testing products | 2 |
| 4.2 | Sensitivity levels | 2 |
| 5 | Testing of penetrant materials | 3 |
| 5.1 | Testing facilities | 3 |
| 5.2 | Reporting | 3 |
| 5.3 | Tests | 4 |
| 6 | Test methods and requirements | 6 |
| 6.1 | Appearance | 6 |
| 6.2 | Penetrant system sensitivity | 6 |
| 6.3 | Density | 11 |
| 6.4 | Viscosity | 11 |
| 6.5 | Flashpoint | 12 |
| 6.6 | Washability (Method A penetrants) | 12 |
| 6.7 | Fluorescent brightness | 12 |
| 6.8 | UV stability | 13 |
| 6.9 | Thermal stability of fluorescent brightness | 13 |
| 6.10 | Water tolerance | 13 |
| 6.11 | Corrosive properties | 14 |
| 6.12 | Content of sulfur and halogens (for products designated low in sulfur and halogens) | 17 |
| 6.13 | Residue on evaporation/solid content | 18 |
| 6.14 | Penetrant tolerance | 18 |
| 6.15 | Developer performance | 18 |
| 6.16 | Redispersability | 18 |
| 6.17 | Density of carrier liquid | 19 |
| 6.18 | Product performance (pressurized containers) | 19 |
| 6.19 | Particle size distribution | 19 |
| 6.20 | Water content | 19 |
| 7 | Packaging and labelling | 19 |
| Annex A (normative) Comparison of fluorescent brightness | | 20 |
| Annex B (normative) Process control tests | | 22 |
| Annex C (informative) Equipment for determination of the visibility of fluorescent indications | | 31 |
| Bibliography | | 32 |