

DIN EN ISO 24817:2025-10 (E)

Erscheinungsdatum: 2025-08-29

Petroleum, petrochemical and natural gas industries - Composite repairs for pipework - Qualification and design, installation, testing and integrity management (ISO/DIS 24817:2025); English version prEN ISO 24817:2025

Contents

	Page
Foreword.....	vi
Introduction.....	vii
1 Scope.....	1
2 Normative references.....	1
3 Terms and definitions.....	2
4 Symbols and abbreviated terms.....	7
4.1 Units.....	7
4.2 Symbols.....	7
4.3 Abbreviated terms.....	11
5 Applications.....	11
6 Summary of key issues.....	13
6.1 Repair system qualification.....	14
6.2 Enquiry stage.....	14
6.3 Design of repair.....	14
6.3.1 Type A and Type B design cases.....	14
6.4 Installer training.....	17
6.5 Installation of repair.....	17
6.6 Ongoing integrity management of the repaired system.....	17
7 Qualification.....	17
7.1 Repair system qualification data.....	17
7.2 Re-qualification of the repair system.....	19
7.2.1 Overview.....	19
7.2.2 For Type A defect repairs.....	19
7.2.3 For Type B defect repairs.....	19
8 Repair feasibility assessment.....	19
8.1 Repair class.....	21
8.2 Required data.....	21
8.2.1 Background.....	21
8.2.2 Original equipment design data.....	21
8.2.3 Maintenance and operational histories.....	22
8.2.4 Service condition data.....	22
9 Design methodology.....	22
9.1 Repair design lifetime and initial service life.....	22
9.2 Environmental compatibility.....	23
9.3 Design temperature effects.....	23
9.4 Cyclic loading.....	25
9.5 Determination of design strains.....	25
9.5.1 Design strains based on default allowable strains.....	25
9.5.2 Design strains based on performance testing.....	26
9.6 Determination of equivalent load and equivalent pressure.....	26
9.7 Design of repairs for Type A defects.....	27
9.7.1 Substrate load sharing, limited by substrate allowable stress.....	27
9.7.2 Substrate load sharing, limited by repair laminate design strain.....	27
9.7.3 Repair laminate carries all loads.....	28
9.8 Design of repairs for Type B defects.....	28

9.8.1	Determination of service factor, f_{leak}	29
9.8.2	Circular or near-circular defects.....	29
9.8.3	Slot-type defects in the circumferential direction.....	30
9.8.4	Slot-type defects in the axial direction.....	30
9.9	External loads.....	30
9.10	Other defects (with assessments based on substrate stress).....	31
9.11	Repair of other components.....	31
9.12	Axial extent of repair.....	32
9.12.1	Patches.....	33
9.13	Calculation of the repair design thickness, t_{design}	34
9.14	Confirmation that repair design thickness is within acceptable limits.....	34
9.14.1	Maximum acceptable value of t_{calc}	34
9.14.2	Maximum allowable design pressure for tees or nozzles.....	34
9.14.3	Potential for repair debonding.....	34
9.15	Calculation of total repair length.....	35
9.16	Design output.....	36
9.17	Optional design considerations.....	36
9.17.1	Fire performance.....	36
9.17.2	Cathodic disbondment.....	36
9.17.3	Electrical conductivity.....	37
9.17.4	Fretting type defects.....	37
9.17.5	Delamination or blister type defects.....	37
9.17.6	Clamps and other repair systems.....	37
10	Installation.....	37
10.1	Storage conditions.....	37
10.2	Documentation prior to repair application.....	38
10.2.1	Method statement.....	38
10.2.2	Work pack.....	38
10.3	Installer and supervisor qualifications.....	40
10.4	Installation procedure.....	40
10.5	Repair completion documentation.....	40
10.6	Live repairs.....	42
10.7	Repair of clamps, piping components, tanks, or vessels.....	42
10.8	Environmental considerations.....	42
10.9	Repair of defects within the repair system.....	42
11	Ongoing integrity management.....	43
11.1	General.....	43
11.2	Record keeping.....	43
11.3	In-service inspection.....	43
11.4	Allowable defects for the repair system.....	45
11.5	Repair system maintenance and remedial options.....	47
11.5.1	Overview.....	47
11.5.2	Substrate adjacent to the repair.....	48
11.5.3	Repairs to Type A defects.....	48
11.5.4	Repairs to Type B defects.....	48
11.5.5	Repair system.....	48
11.6	Repair lifetime considerations.....	49
11.6.1	Periodic review.....	49
11.6.2	Lifetime reduction.....	50
11.6.3	Lifetime extension.....	50
11.7	Future modifications.....	50
12	System testing.....	50
13	Decommissioning.....	51
Annex A (normative)	Design data sheet.....	52
Annex B (normative)	Qualification data.....	55
Annex C (normative)	Short-term pipe spool survival test.....	60
Annex D (normative)	Measurement of γ_{LCL} for through-wall defect calculation.....	62
Annex E (normative)	Measurement of performance test data.....	67
Annex F (normative)	Measurement of impact performance.....	69

Annex G (normative) Measurement of the degradation factor 70

Annex H (normative) Qualification of repair systems for other defects (with assessments based on substrate stress) 72

Annex I (Informative) Guidance on the selection of the appropriate defect size and geometry for through-wall defects (Type B defect) 75

Annex J (normative) Installer qualification 84

Annex K (informative) Installation requirements and guidance 87

Annex L (informative) Design considerations 89

Annex M (informative) Management of the integrity of composite repair systems to pipework and vessels 96

Bibliography 99