

ISO 13704:2007-11 (E)

Petroleum, petrochemical and natural gas industries - Calculation of heater-tube thickness in petroleum refineries

Contents		Page
Foreword		iv
1	Scope	1
2	Terms and definitions	1
3	General design information	3
3.1	Information required	3
3.2	Limitations for design procedures	4
4	Design	4
4.1	General	4
4.2	Equation for stress	7
4.3	Elastic design (lower temperatures)	7
4.4	Rupture design (higher temperatures)	8
4.5	Intermediate temperature range	8
4.6	Minimum allowable thickness	8
4.7	Minimum and average thicknesses	8
4.8	Equivalent tube metal temperature	9
4.9	Component fittings	13
5	Allowable stresses	15
5.1	General	15
5.2	Elastic allowable stress	16
5.3	Rupture allowable stress	16
5.4	Rupture exponent	16
5.5	Yield and tensile strengths	16
5.6	Larson-Miller parameter curves	16
5.7	Limiting design metal temperature	17
5.8	Allowable stress curves	17
6	Sample calculations	18
6.1	Elastic design	18
6.2	Thermal-stress check (for elastic range only)	19
6.3	Rupture design with constant temperature	23
6.4	Rupture design with linearly changing temperature	25
Annex A (informative) Estimation of remaining tube life		28
Annex B (informative) Calculation of maximum radiant section tube skin temperature		33
Annex C (normative) Thermal-stress limitations (elastic range)		44
Annex D (informative) Calculation sheets		48
Annex E (normative) Stress curves (SI units)		50
Annex F (normative) Stress curves (USC units)		70
Annex G (normative) Derivation of corrosion fraction and temperature fraction		90
Annex H (informative) Data sources		98
Bibliography		103