

ISO 10416:2008-06 (E)

Petroleum and natural gas industries - Drilling fluids - Laboratory testing

Contents		Page
Foreword		vii
Introduction		viii
1	Scope	1
2	Normative references	1
3	Terms and definitions	2
4	Symbols and abbreviations	3
5	Barite	6
5.1	Principle	6
5.2	Reagents and apparatus	6
5.3	Sampling	7
5.4	Calculation of moisture content	7
5.5	Sieve analysis	7
5.6	Sedimentation analysis	8
6	Barite performance	12
6.1	Principle	12
6.2	Reagents and apparatus	12
6.3	Base drilling fluid preparation	13
6.4	Rheology test	13
6.5	Calculation	14
7	Abrasiveness of weighting materials	14
7.1	Principle	14
7.2	Reagents and apparatus	15
7.3	Determination of abrasion	15
8	Mercury in drilling fluid barite	17
8.1	Principle	17
8.2	Reagents and apparatus	17
8.3	Preparation of standards	19
8.4	Sample digestion	19
8.5	Check for recovery of Hg during digestion	20
8.6	Analysis of standards and samples	20
8.7	Calculation	20
9	Cadmium and lead in drilling fluid barite	21
9.1	Principle	21
9.2	Reagents and apparatus	21
9.3	Preparation of combined cadmium and lead standards	22
9.4	Sample digestion	22
9.5	Analysis of standards and samples	22
9.6	Calculation	23
10	Arsenic in drilling fluid barite	23
10.1	Principle	23
10.2	Reagents and apparatus	24

10.3	Preparation of standards	25
10.4	Sample digestion	25
10.5	Analysis of standards and samples	26
10.6	Calculation	26
11	Bridging materials for regaining circulation	26
11.1	Principle	26
11.2	Apparatus	27
11.3	Preparation of test drilling fluid	27
11.4	Static slot test	27
11.5	Dynamic slot test	28
11.6	Static marble bed test	28
11.7	Dynamic marble bed test	28
11.8	Static ball bearings (BB shot) bed test	29
11.9	Dynamic ball bearings (BB shot) bed test	29
12	Filtration-control agents	29
12.1	Principle	29
12.2	Reagents and apparatus	29
12.3	General instructions for preparation of base drilling fluids	31
12.4	Salt-saturated drilling fluid	31
12.5	High-hardness, salt-saturated drilling fluid	32
12.6	10 % potassium chloride (KCl) drilling fluid	32
12.7	Pre-hydrated bentonite slurry	33
12.8	Modified seawater drilling fluid	33
12.9	Low-salinity drilling fluid	33
12.10	Lime-treated drilling fluid	34
12.11	Low solids, non-dispersed drilling fluid	34
12.12	Freshwater lignosulfonate drilling fluid	35
12.13	Initial performance test	35
12.14	Performance after heat ageing	36
13	Methylene blue test for drilled solids and commercial bentonite	36
13.1	Methylene blue capacity of drill solids	36
13.2	Methylene blue capacity of commercial bentonite	39
13.3	Solids content	40
14	Deflocculation test for thinner evaluation	41
14.1	Principle	41
14.2	Reagents and apparatus	42
14.3	Procedure for moisture content	43
14.4	Calculation of moisture content	43
14.5	Preparation of drilling fluid base	43
14.6	Calculation	44
14.7	Determination of rheological properties	44
14.8	Calculation of thinner efficiency	46
15	Testing base oils used in drilling fluids	46
15.1	General	46
15.2	Reagents and apparatus	46
15.3	Density, relative density (specific gravity), or API gravity-hydrometer method (see ISO 3675)	46
15.4	Density and relative density of liquids using a digital density meter (see ASTM D 4052) ...	47
15.5	Kinematic viscosity of transparent and opaque oils -- Calibrated capillary tube method (see ISO 3104)	47
15.6	Distillation (see ISO 3405)	47
15.7	Aniline point and mixed aniline point (see ISO 2977:1997)	48
15.8	Pour point (see ISO 3016)	48
15.9	Flash point by Pensky-Martens closed tester (see ISO 2719)	49
15.10	Aromatics content (see IP 391 or ASTM D 5186)	49
16	Potassium ion content -- Ion-selective electrode method	50
16.1	Principle	50
16.2	Reagents and apparatus	50
16.3	Preparation of electrodes	51
16.4	Operational check of electrode system	51
16.5	Measurements using a meter with direct concentration readout capability	52

16.6	Measurements with instruments that provide either a digital or an analogue readout in millivolts	52
17	Calcium ion content -- Ion-selective electrode method	53
17.1	Principle	53
17.2	Reagents and apparatus	53
17.3	Preparation of electrodes	54
17.4	Operational check of electrode system	55
17.5	Measurements using a meter with direct concentration readout capability	55
17.6	Measurements with instruments that provide either a digital or an analogue readout in millivolts	55
18	Sodium ion content -- Ion-selective electrode method	56
18.1	Principle	56
18.2	Reagents and apparatus	57
18.3	Preparation and operational check of the electrode system	57
18.4	Measurements using a meter with a direct concentration-readout capability	58
18.5	Measurements using a meter with readout in millivolts	58
19	Density of solids -- Stereopycnometer method	59
19.1	Principle	59
19.2	Apparatus	59
19.3	Procedure -- Stereopycnometer method	59
19.4	Calculation -- Stereopycnometer method	60
20	Density of solids -- Air comparison pycnometer method	61
20.1	Principle	61
20.2	Apparatus	61
20.3	Procedure -- Air comparison pycnometer method	61
20.4	Calculation -- Air comparison pycnometer method	61
21	Ageing of water-based drilling fluids	62
21.1	Principle	62
21.2	Practices common to preparation, handling and testing over all temperature ranges	62
21.3	Drilling fluid sample preparation and ageing at ambient temperature	63
21.4	Drilling fluid ageing at moderate temperatures [ambient to 65 °C (150 °F)]	64
21.5	Drilling fluid ageing at substantially elevated temperatures [over 65 °C (150 °F)]	66
21.6	Inertness and chemical compatibility in high-temperature ageing cells	68
21.7	Obtaining supplies and services for the ageing of drilling fluid samples	69
22	Ageing of oil-based drilling fluids	69
22.1	Principle	69
22.2	Apparatus	70
22.3	Practices common to preparation, handling and testing over all temperature ranges	71
22.4	Drilling fluid ageing at ambient temperatures	72
22.5	Drilling fluid ageing at moderate temperatures [ambient to 65 °C (150 °F)]	73
22.6	Drilling fluid ageing at substantially elevated temperatures [over 65 °C (150 °F)]	74
22.7	Inertness and chemical compatibility in high-temperature ageing cells	75
22.8	Obtaining supplies and services for the ageing of drilling fluid samples	76
23	Shale-particle disintegration test by hot rolling	76
23.1	Principle	76
23.2	Reagents and apparatus	77
23.3	Procedure	77
23.4	Calculation	78
24	Drilling fluid materials -- High-viscosity polyanionic cellulose (PAC-HV) (regular)	79
24.1	Principle	79
24.2	Determination of moisture content	79
24.3	Procedures with test fluid containing PAC-HV	80
25	Drilling fluid materials -- Low-viscosity polyanionic cellulose (PAC-LV)	82
25.1	Principle	82
25.2	Determination of moisture content	83
25.3	Procedures with test fluid containing PAC-LV	83
26	Preparation and evaluation of invert-emulsion drilling fluids	86
26.1	Principle	86
26.2	Reagents and apparatus	86
26.3	Mixing of the initial drilling fluid	87
26.4	Testing the properties of the initial drilling fluid	88

26.5	Preparation of the sample contaminated by seawater	88
26.6	Preparation of the sample contaminated by base evaluation clay	89
26.7	Preparation of the sample contaminated by mixed-salt brine	89
26.8	Procedure for hot-rolling	89
26.9	Procedure for static ageing	89
26.10	Procedure for testing after heat ageing	90
27	High-temperature/high-pressure filtration testing of drilling fluids using the permeability plugging apparatus and cells with set-screw-secured end caps	90
27.1	Principle	90
27.2	Safety considerations	90
27.3	Apparatus -- Permeability-plugging apparatus (PPA) with set-screw-secured end caps	92
27.4	Procedure for high-temperature/high-pressure (HTHP) filtration	94
27.5	Test conclusion and disassembly	97
27.6	Data reporting	99
28	High-temperature/high-pressure filtration testing of drilling fluids using the permeability-plugging apparatus and cells with threaded end caps	100
28.1	Principle	100
28.2	Safety considerations	100
28.3	Apparatus -- Permeability-plugging apparatus (PPA) with threaded end caps	102
28.4	Procedure for high-temperature/high-pressure (HTHP) filtration	104
28.5	Test conclusion and disassembly	106
28.6	Data reporting	108
Bibliography		109