

DIN EN ISO 10416:2010-04 (E)

Petroleum and natural gas industries - Drilling fluids - Laboratory testing (ISO 10416:2008); English version EN ISO 10416:2009

Inhalt	Seite
Foreword	6
Introduction.....	7
1 Scope	8
2 Normative references	8
3 Terms and definitions	9
4 Symbols and abbreviations	10
5 Barite.....	13
5.1 Principle	13
5.2 Reagents and apparatus.....	13
5.3 Sampling	14
5.4 Calculation of moisture content	14
5.5 Sieve analysis	14
5.6 Sedimentation analysis.....	15
6 Barite performance.....	21
6.1 Principle	21
6.2 Reagents and apparatus.....	22
6.3 Base drilling fluid preparation	23
6.4 Rheology test.....	23
6.5 Calculation	24
7 Abrasiveness of weighting materials	24
7.1 Principle	24
7.2 Reagents and apparatus.....	24
7.3 Determination of abrasion.....	25
8 Mercury in drilling fluid barite.....	27
8.1 Principle	27
8.2 Reagents and apparatus.....	27
8.3 Preparation of standards	29
8.4 Sample digestion.....	29
8.5 Check for recovery of Hg during digestion	30
8.6 Analysis of standards and samples	30
8.7 Calculation	30
9 Cadmium and lead in drilling fluid barite.....	31
9.1 Principle	31
9.2 Reagents and apparatus.....	31
9.3 Preparation of combined cadmium and lead standards	32
9.4 Sample digestion.....	32
9.5 Analysis of standards and samples	32
9.6 Calculation	33
10 Arsenic in drilling fluid barite.....	33
10.1 Principle	33
10.2 Reagents and apparatus.....	34
10.3 Preparation of standards	35
10.4 Sample digestion.....	35
10.5 Analysis of standards and samples	36
10.6 Calculation	36

11	Bridging materials for regaining circulation	36
11.1	Principle	36
11.2	Apparatus	37
11.3	Preparation of test drilling fluid	37
11.4	Static slot test	37
11.5	Dynamic slot test	38
11.6	Static marble bed test	38
11.7	Dynamic marble bed test	38
11.8	Static ball bearings (BB shot) bed test.....	39
11.9	Dynamic ball bearings (BB shot) bed test	39
12	Filtration-control agents	39
12.1	Principle	39
12.2	Reagents and apparatus	39
12.3	General instructions for preparation of base drilling fluids.....	41
12.4	Salt-saturated drilling fluid	41
12.5	High-hardness, salt-saturated drilling fluid	42
12.6	10 % potassium chloride (KCl) drilling fluid	42
12.7	Pre-hydrated bentonite slurry	43
12.8	Modified seawater drilling fluid	43
12.9	Low-salinity drilling fluid	43
12.10	Lime-treated drilling fluid.....	44
12.11	Low solids, non-dispersed drilling fluid.....	44
12.12	Freshwater lignosulfonate drilling fluid	45
12.13	Initial performance test	45
12.14	Performance after heat ageing	46
13	Methylene blue test for drilled solids and commercial bentonite	46
13.1	Methylene blue capacity of drill solids.....	46
13.2	Methylene blue capacity of commercial bentonite.....	51
13.3	Solids content	52
14	Deflocculation test for thinner evaluation.....	53
14.1	Principle	53
14.2	Reagents and apparatus	54
14.3	Procedure for moisture content.....	55
14.4	Calculation of moisture content.....	55
14.5	Preparation of drilling fluid base.....	56
14.6	Calculation.....	56
14.7	Determination of rheological properties	57
14.8	Calculation of thinner efficiency	58
15	Testing base oils used in drilling fluids	58
15.1	General.....	58
15.2	Reagents and apparatus	58
15.3	Density, relative density (specific gravity), or API gravity-hydrometer method (see ISO 3675).....	59
15.4	Density and relative density of liquids using a digital density meter (see ASTM D 4052)	59
15.5	Kinematic viscosity of transparent and opaque oils — Calibrated capillary tube method (see ISO 3104).....	59
15.6	Distillation (see ISO 3405)	60
15.7	Aniline point and mixed aniline point (see ISO 2977:1997)	60
15.8	Pour point (see ISO 3016)	60
15.9	Flash point by Pensky-Martens closed tester (see ISO 2719).....	61
15.10	Aromatics content (see IP 391 or ASTM D 5186).....	61
16	Potassium ion content — Ion-selective electrode method	62
16.1	Principle.....	62
16.2	Reagents and apparatus	62
16.3	Preparation of electrodes	63
16.4	Operational check of electrode system.....	64
16.5	Measurements using a meter with direct concentration readout capability	64
16.6	Measurements with instruments that provide either a digital or an analogue readout in millivolts	64

17	Calcium ion content — Ion-selective electrode method	65
17.1	Principle	65
17.2	Reagents and apparatus.....	65
17.3	Preparation of electrodes	67
17.4	Operational check of electrode system	67
17.5	Measurements using a meter with direct concentration readout capability.....	67
17.6	Measurements with instruments that provide either a digital or an analogue readout in millivolts	68
18	Sodium ion content — Ion-selective electrode method	68
18.1	Principle	68
18.2	Reagents and apparatus.....	69
18.3	Preparation and operational check of the electrode system	70
18.4	Measurements using a meter with a direct concentration-readout capability.....	70
18.5	Measurements using a meter with readout in millivolts	71
19	Density of solids — Stereopycnometer method	71
19.1	Principle	71
19.2	Apparatus.....	72
19.3	Procedure — Stereopycnometer method	72
19.4	Calculation — Stereopycnometer method.....	73
20	Density of solids — Air comparison pycnometer method	73
20.1	Principle	73
20.2	Apparatus.....	73
20.3	Procedure — Air comparison pycnometer method	73
20.4	Calculation — Air comparison pycnometer method	74
21	Ageing of water-based drilling fluids	74
21.1	Principle	74
21.2	Practices common to preparation, handling and testing over all temperature ranges	75
21.3	Drilling fluid sample preparation and ageing at ambient temperature	76
21.4	Drilling fluid ageing at moderate temperatures [ambient to 65 °C (150 °F)]	77
21.5	Drilling fluid ageing at substantially elevated temperatures [over 65 °C (150 °F)].....	78
21.6	Inertness and chemical compatibility in high-temperature ageing cells.....	80
21.7	Obtaining supplies and services for the ageing of drilling fluid samples.....	81
22	Ageing of oil-based drilling fluids	82
22.1	Principle	82
22.2	Apparatus.....	82
22.3	Practices common to preparation, handling and testing over all temperature ranges	84
22.4	Drilling fluid ageing at ambient temperatures.....	85
22.5	Drilling fluid ageing at moderate temperatures [ambient to 65 °C (150 °F)]	85
22.6	Drilling fluid ageing at substantially elevated temperatures [over 65 °C (150 °F)].....	86
22.7	Inertness and chemical compatibility in high-temperature ageing cells.....	88
22.8	Obtaining supplies and services for the ageing of drilling fluid samples.....	88
23	Shale-particle disintegration test by hot rolling.....	89
23.1	Principle	89
23.2	Reagents and apparatus.....	89
23.3	Procedure	90
23.4	Calculation	91
24	Drilling fluid materials — High-viscosity polyanionic cellulose (PAC-HV) (regular).....	91
24.1	Principle	91
24.2	Determination of moisture content.....	92
24.3	Procedures with test fluid containing PAC-HV	92
25	Drilling fluid materials — Low-viscosity polyanionic cellulose (PAC-LV).....	95
25.1	Principle	95
25.2	Determination of moisture content.....	96
25.3	Procedures with test fluid containing PAC-LV.....	96
26	Preparation and evaluation of invert-emulsion drilling fluids	99
26.1	Principle	99
26.2	Reagents and apparatus.....	99

26.3	Mixing of the initial drilling fluid.....	100
26.4	Testing the properties of the initial drilling fluid	101
26.5	Preparation of the sample contaminated by seawater	101
26.6	Preparation of the sample contaminated by base evaluation clay.....	102
26.7	Preparation of the sample contaminated by mixed-salt brine	102
26.8	Procedure for hot-rolling	102
26.9	Procedure for static ageing	102
26.10	Procedure for testing after heat ageing	103
27	High-temperature/high-pressure filtration testing of drilling fluids using the permeability plugging apparatus and cells with set-screw-secured end caps	103
27.1	Principle	103
27.2	Safety considerations	103
27.3	Apparatus — Permeability-plugging apparatus (PPA) with set-screw-secured end caps.....	105
27.4	Procedure for high-temperature/high-pressure (HTHP) filtration.....	107
27.5	Test conclusion and disassembly	110
27.6	Data reporting	112
28	High-temperature/high-pressure filtration testing of drilling fluids using the permeability- plugging apparatus and cells with threaded end caps.....	113
28.1	Principle	113
28.2	Safety considerations	113
28.3	Apparatus — Permeability-plugging apparatus (PPA) with threaded end caps	115
28.4	Procedure for high-temperature/high-pressure (HTHP) filtration.....	117
28.5	Test conclusion and disassembly	119
28.6	Data reporting	121
	Bibliography	122