

# DIN EN ISO 13503-2:2010-03 (E)

Petroleum and natural gas industries - Completion fluids and materials - Part 2: Measurement of properties of proppants used in hydraulic fracturing and gravel-packing operations (ISO 13503-2:2006 + Amd 1:2009); English version EN ISO 13503-2:2006 + A1:2009

---

Inhalt	Seite
Foreword .....	4
<b>A<sub>1</sub></b> Foreword .....	5
Introduction .....	6
1 Scope .....	7
2 Normative references .....	7
3 Abbreviations .....	7
4 Standard proppant sampling procedure .....	7
4.1 General .....	7
4.2 Particle segregation .....	8
4.3 Equipment .....	8
4.4 Number of required samples — Bulk .....	11
4.4.1 Proppants for hydraulic fracturing .....	11
4.4.2 Gravel-packing media .....	11
4.5 Sampling — Bulk material .....	12
4.6 Sampling — Bagged material .....	12
4.6.1 Bags up to 50 kg (110 lb) .....	12
4.6.2 Totes/bulk bags/super sacks weighing up to 2 000 kg (4 400 lb) .....	12
5 Sample handling and storage .....	12
5.1 Sample reduction .....	12
5.2 Sample splitting .....	12
5.3 Sample and record retention and storage .....	12
6 Sieve analysis .....	13
6.1 Purpose .....	13
6.2 Description .....	13
6.3 Equipment and materials .....	13
6.4 Procedure .....	13
6.5 Calculation of the mean diameter, median diameter and standard deviation .....	14
6.5.1 General .....	14
6.5.2 Mean diameter .....	14
6.5.3 Median diameter .....	15
6.6 Sieve calibration .....	16
6.6.1 Purpose .....	16
6.6.2 Description .....	16
6.6.3 Procedure .....	17
6.6.4 Preparing calibration samples .....	18
7 Proppant sphericity and roundness .....	18
7.1 Purpose .....	18
7.2 Description .....	19
7.3 Apparatus capability .....	19
7.4 Procedure .....	19
7.5 Alternate method for determining average sphericity and roundness .....	20
7.5.1 Use of photomicrographs .....	20
7.5.2 Procedure .....	20

7.5.3	Suggested magnification for photomicrographs .....	20
8	Acid solubility .....	20
8.1	Purpose.....	20
8.2	Description .....	20
8.3	Equipment and materials .....	21
8.4	Procedure .....	21
8.4.1	General.....	21
8.4.2	Preparation of 12:3 HCl:HF solution .....	21
8.4.3	Solubility test .....	22
9	Turbidity test .....	22
9.1	Purpose.....	22
9.2	Description .....	23
9.3	Equipment and materials .....	23
9.4	Equipment calibration .....	23
9.5	Procedure .....	23
10	Procedures for determining proppant bulk density, apparent density and absolute density.....	24
10.1	Purpose.....	24
10.2	Description .....	24
10.3	Bulk density.....	24
10.3.1	Equipment and materials .....	24
10.3.2	Calibration of cylinder .....	25
10.3.3	Procedure .....	26
10.4	Apparent density.....	26
10.4.1	Equipment and materials .....	26
10.4.2	Procedure .....	27
10.5	Absolute density .....	28
10.5.1	Description .....	28
10.5.2	Equipment .....	28
10.5.3	Procedures .....	28
11	Proppant crush-resistance test.....	28
11.1	Purpose.....	28
11.2	Description .....	29
11.3	Equipment and materials .....	29
11.4	Sample preparation .....	29
11.5	Crush-resistance procedure.....	30
12	Loss on ignition of resin-coated proppant .....	32
12.1	Objective.....	32
12.2	Apparatus and materials.....	32
12.3	Loss-on-ignition procedure for whole-grain proppant .....	32
Annex A	(informative) Formazin solution preparation .....	34
A.1	Preparation of a formazin polymer solution for calibration .....	34
A.2	Equipment Calibration .....	34
Annex B	(informative) Proppant specifications .....	35
B.1	Fracturing proppant sizes.....	35
B.2	Gravel packing sizes .....	36
B.3	Sphericity and roundness.....	36
B.4	Acid solubility .....	37
B.5	Maximum proppant turbidity .....	37
B.6	Maximum crush material.....	37
B.6.1	General.....	37
B.6.2	Gravel packing proppants .....	37
B.6.3	Fracturing proppants .....	38
Bibliography	.....	39