

ISO 12212:2012-08 (E)

Petroleum, petrochemical and natural gas industries - Hairpin-type heat exchangers

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Normative reference	1
3	Terms and definitions	1
4	General	3
5	Proposal information required	4
6	Drawings and other required data	4
6.1	Outline drawings and other supporting data	4
6.2	Information required after outline drawings are reviewed	5
6.3	Reports and records	6
7	Design	7
7.1	Design temperature	7
7.2	Design pressure	7
7.3	Cyclic design	7
7.4	Shell	8
7.5	Front closure	8
7.6	Rear closure	10
7.7	Tube bundle	11
7.8	Nozzles and other connections	14
7.9	Shell supports	18
7.10	Gaskets	19
7.11	Flanged external girth joints	19
7.12	Cladding for corrosion allowance	19
8	Materials	20
8.1	General	20
8.2	Requirements for carbon steel in sour or wet hydrogen sulfide service	20
8.3	Gaskets	20
8.4	Tubes	20
9	Fabrication	21
9.1	Shells	21
9.2	Tubes	21
9.3	Welding	21
9.4	Heat treatment	22
9.5	Dimensional tolerances	22
9.6	Gasket contact surfaces other than nozzle flange facings	23
9.7	Tube-to-tubesheet joints	23
9.8	Assembly	24
10	Inspection and testing	24
10.1	Quality assurance	24
10.2	Quality control	24

10.3	Pressure testing	26
10.4	Nameplates and stampings	26
11	Preparation for shipment	27
11.1	Protection	27
11.2	Identification	27
12	Supplemental requirements	28
12.1	General	28
12.2	Design	28
12.3	Examination	28
Annex A (informative) Recommended practices		30
Annex B (informative) Hairpin heat exchanger checklist		32
Annex C (informative) Hairpin heat exchanger data sheets		34
Bibliography		45