ISO 12212:2012-08 (E)

Petroleum, petrochemical and natural gas industries - Hairpin-type heat exchangers

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Normative reference 1

3 Terms and definitions 1

4 General 3

5 Proposal information required 4

6 Drawings and other required data 4
6.1 Outline drawings and other supporting data 4
6.2 Information required after outline drawings are reviewed 5
6.3 Reports and records 6

7 Design 7
7.1 Design temperature 7
7.2 Design pressure 7
7.3 Cyclic design 7
7.4 Shell 8
7.5 Front closure 8
7.6 Rear closure 10
7.7 Tube bundle 11
7.8 Nozzles and other connections 14
7.9 Shell supports 18
7.10 Gaskets 19
7.11 Flanged external girth joints 19
7.12 Cladding for corrosion allowance 19

8 Materials 20
8.1 General 20
8.2 Requirements for carbon steel in sour or wet hydrogen sulfide service 20
8.3 Gaskets 20
8.4 Tubes 20

9 Fabrication 21
9.1 Shells 21
9.2 Tubes 21
9.3 Welding 21
9.4 Heat treatment 22
9.5 Dimensional tolerances 22
9.6 Gasket contact surfaces other than nozzle flange facings 23
9.7 Tube-to-tubesheet joints 23
9.8 Assembly 24

10 Inspection and testing 24
10.1 Quality assurance 24
10.2 Quality control 24

10.3 Pressure testing 26
10.4 Nameplates and stampings 26

11 Preparation for shipment 27
11.1 Protection 27
11.2 Identification 27

12 Supplemental requirements 28
12.1 General 28
12.2 Design 28
12.3 Examination 28

Annex A (informative) Recommended practices 30

Annex B (informative) Hairpin heat exchanger checklist 32

Annex C (informative) Hairpin heat exchanger data sheets 34

Bibliography 45