

ISO 19901-3:2014-12 (E)

Petroleum and natural gas industries - Specific requirements for offshore structures - Part 3: Topsides structure

Contents		Page
Foreword		v
Introduction		vii
1	Scope	1
2	Normative references	2
3	Terms and definitions	2
4	Symbols and abbreviated terms	6
4.1	Symbols	6
4.2	Abbreviated terms	8
5	Overall considerations	9
5.1	Design situations	9
5.2	Codes and standards	9
5.3	Deck elevation and green water	10
5.4	Exposure level	10
5.5	Operational considerations	10
5.6	Selecting the design environmental conditions	11
5.7	Assessment of existing topsides structures	11
5.8	Reuse of topsides structure	11
5.9	Modifications and refurbishment	11
6	Design requirements	11
6.1	General	11
6.2	Materials selection	11
6.3	Design conditions	11
6.4	Structural interfaces	12
6.5	Design for serviceability limit states (SLS)	12
6.6	Design for ultimate limit states (ULS)	14
6.7	Design for fatigue limit states (FLS)	15
6.8	Design for accidental limit states (ALS)	15
6.9	Robustness	15
6.10	Corrosion control	16
6.11	Design for fabrication and inspection	16
6.12	Design considerations for structural integrity management	17
6.13	Design for decommissioning, removal and disposal	17
7	Actions	17
7.1	General	17
7.2	In-place actions	18
7.3	Action factors	20
7.4	Vortex-induced vibrations	21
7.5	Deformations	21
7.6	Wave and current actions	22
7.7	Wind actions	22
7.8	Seismic actions	22
7.9	Actions during fabrication and installation	24
7.10	Accidental situations	24

7.11	Other actions	34
8	Strength and resistance of structural components	36
8.1	Use of local building standards	36
8.2	Cylindrical tubular member design	36
8.3	Design of non-cylindrical sections	37
8.4	Connections	37
8.5	Castings	38
9	Structural systems	39
9.1	Topsides design	39
9.2	Topsides structure design models	39
9.3	Support structure interface	40
9.4	Flare towers, booms, vents and similar structures	40
9.5	Helicopter landing facilities (helidecks)	41
9.6	Crane support structure	44
9.7	Derrick design	47
9.8	Bridges	47
9.9	Bridge bearings	48
9.10	Anti-vibration mountings for modules and major equipment skids	48
9.11	System interface assumptions	48
9.12	Fire protection systems	49
9.13	Penetrations	49
9.14	Difficult-to-inspect areas	49
9.15	Drainage	49
9.16	Actions due to drilling operations	49
9.17	Strength reduction due to heat	49
9.18	Walkways, laydown areas and equipment maintenance	50
9.19	Muster areas and lifeboat stations	50
10	Materials	50
10.1	General	50
10.2	Carbon steel	51
10.3	Stainless steel	53
10.4	Aluminium alloys	54
10.5	Fibre-reinforced composites	55
10.6	Timber	55
11	Fabrication, quality control, quality assurance and documentation	55
11.1	Assembly	55
11.2	Welding	56
11.3	Fabrication inspection	56
11.4	Quality control, quality assurance and documentation	56
11.5	Corrosion protection	57
12	Corrosion control	57
12.1	General	57
12.2	Forms of corrosion, associated corrosion rates and corrosion damage	57
12.3	Design of corrosion control	57
12.4	Fabrication and installation of corrosion control	58
12.5	In-service inspection, monitoring and maintenance of corrosion control	59
13	Loadout, transportation and installation	59
14	In-service inspection and structural integrity management	60
14.1	General	60
14.2	Particular considerations applying to topsides structures	60
14.3	Topsides structure default inspection scopes	61
15	Assessment of existing topsides structures	62
16	Reuse of topsides structure	63

Annex A (informative) Additional information and guidance 64
Annex B (informative) Example calculation of building code correspondence factor 108
Annex C (informative) Regional information 114
Bibliography 115