ISO 15156-2:2015-09 (E)

Petroleum and natural gas industries - Materials for use in H2S-containing environments in oil and gas production - Part 2: Cracking-resistant carbon and low-alloy steels, and the use of cast irons

Contents

Page

Foreword ..... **iv**

Introduction ..... **v**

1 Scope **1**

2 Normative references **2**

3 Terms and definitions **3**

4 Symbols and abbreviated terms **6**

5 Purchasing information **6**

6 Factors affecting the behaviour of carbon and low alloy steels in H_2S-containing environments **7**

7 Qualification and selection of carbon and low-alloy steels with resistance to SSC, SOHIC and SZC **8**

7.1 Option 1 — Selection of SSC-resistant steels (and cast irons) using A.2 8

7.1.1 For p_{H2S} < 0,3 kPa (0,05 psi) 8

7.1.2 For p_{H2S} ≥ 0,3 kPa (0,05 psi) 8

7.2 Option 2 — Selection of steels for specific sour-service applications or for ranges of sour service 8

7.2.1 Sulfide stress-cracking 8

7.2.2 SOHIC and SZC 10

7.3 Hardness requirements 10

7.3.1 General 10

7.3.2 Parent metals 10

7.3.3 Welds 10

7.4 Other fabrication methods 16

8 Evaluation of carbon and low alloy steels for their resistance to HIC/SWC **16**

9 Marking, labelling, and documentation **17**

Annex A (normative) **SSC-resistant carbon and low alloy steels (and requirements and recommendations for the use of cast irons)** **18**

Annex B (normative) **Qualification of carbon and low-alloy steels for H_2S service by laboratory testing** **27**

Annex C (informative) **Determination of H_2S partial pressure** **35**

Annex D (informative) **Recommendations for determining pH** **37**

Annex E (informative) **Information that should be supplied for material purchasing** **42**

Bibliography **44**