

ISO 15156-2:2015-09 (E)

Petroleum and natural gas industries - Materials for use in H₂S-containing environments in oil and gas production - Part 2: Cracking-resistant carbon and low-alloy steels, and the use of cast irons

Contents		Page
Foreword		iv
Introduction		v
1 Scope		1
2 Normative references		2
3 Terms and definitions		3
4 Symbols and abbreviated terms		6
5 Purchasing information		6
6 Factors affecting the behaviour of carbon and low alloy steels in H₂S-containing environments		7
7 Qualification and selection of carbon and low-alloy steels with resistance to SSC, SOHIC and SZC		8
7.1 Option 1 — Selection of SSC-resistant steels (and cast irons) using A.2.....		8
7.1.1 For $p_{\text{H}_2\text{S}} < 0,3$ kPa (0,05 psi).....		8
7.1.2 For $p_{\text{H}_2\text{S}} \geq 0,3$ kPa (0,05 psi).....		8
7.2 Option 2 — Selection of steels for specific sour-service applications or for ranges of sour service.....		8
7.2.1 Sulfide stress-cracking.....		8
7.2.2 SOHIC and SZC.....		10
7.3 Hardness requirements.....		10
7.3.1 General.....		10
7.3.2 Parent metals.....		10
7.3.3 Welds.....		10
7.4 Other fabrication methods.....		16
8 Evaluation of carbon and low alloy steels for their resistance to HIC/SWC		16
9 Marking, labelling, and documentation		17
Annex A (normative) SSC-resistant carbon and low alloy steels (and requirements and recommendations for the use of cast irons)		18
Annex B (normative) Qualification of carbon and low-alloy steels for H₂S service by laboratory testing		27
Annex C (informative) Determination of H₂S partial pressure		35
Annex D (informative) Recommendations for determining pH		37
Annex E (informative) Information that should be supplied for material purchasing		42
Bibliography		44