

Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms, definitions, symbols and abbreviated terms
3.1	Terms and definitions
3.2	Symbols and abbreviated terms
4	Conformance
4.1	Dual citing of normative references
4.2	Units of measurement
5	Information to be supplied when placing orders for drill-pipe
5.1	Grades D95 and F105
5.2	General information
5.3	Additional information
6	Requirements for drill-pipe
6.1	General
6.2	Dimensions, masses and connections
6.2.1	Standard configuration
6.2.2	Alternative configurations
6.2.3	Drill-pipe weld neck diameters
6.2.4	Tool-joint inside diameters
6.2.5	Length
6.2.6	Length of tool-joint outside diameter
6.2.7	End-drift
6.2.8	Drill-pipe body and tool-joint alignment
6.2.9	Weld-zone profile
6.3	Material requirements
6.3.1	General
6.3.2	Weld-zone yield strength
6.3.3	Weld-zone hardness
6.3.3.1	Grades E, X, G and S
6.3.3.2	Grades D and F
6.3.4	Weld-zone Charpy V-notch absorbed-energy requirements
6.3.5	Weld-zone Charpy V-notch absorbed energy — Alternative requirements
6.3.6	Weld-zone transverse side bend properties
6.3.7	Sulfide stress cracking test — Grades D and F
6.3.7.1	85 % SMYS all parts (default)
6.3.7.2	Alternative testing (by agreement between purchaser and manufacturer)
6.4	Process of manufacture for drill-pipe
6.4.1	Processes requiring validation
6.4.2	Welding qualification
6.4.3	Welding of tool joints to drill-pipe body and post-weld heat treatment
6.4.4	Weld machining
6.4.5	Internal coating
6.4.6	External coating
6.4.7	Thread protection
6.5	Traceability
6.6	Testing — General

- 6.6.1 Test equipment calibration
 - 6.6.2 Dimensional inspection
 - 6.6.3 Drill-pipe length
 - 6.6.4 Straightness
 - 6.6.5 End-drift test
 - 6.6.6 Internal profile
 - 6.6.7 Drill-pipe body and tool-joint alignment
 - 6.7 Testing of welds
 - 6.7.1 Lot size
 - 6.7.2 Test specimens
 - 6.8 Tensile test
 - 6.8.1 Procedures
 - 6.8.2 Test equipment calibration
 - 6.8.3 Specimens
 - 6.8.4 Frequency
 - 6.8.5 Defective specimen
 - 6.8.6 Re-tests
 - 6.9 Hardness test
 - 6.9.1 Procedures
 - 6.9.2 Surface hardness test
 - 6.9.3 Surface hardness — Re-test
 - 6.9.4 Through-wall hardness test
 - 6.9.5 Through-wall hardness — Re-tests
 - 6.10 Charpy V-notch impact test
 - 6.10.1 Procedures
 - 6.10.2 Specimen size and orientation
 - 6.10.3 Test frequency
 - 6.10.4 Re-tests
 - 6.10.5 Defective specimens
 - 6.11 Transverse side-bend test
 - 6.11.1 Procedure
 - 6.11.2 Specimens
 - 6.11.3 Test frequency
 - 6.11.4 Re-tests
 - 6.12 Imperfections and defects in drill-pipe
 - 6.12.1 General
 - 6.12.2 Weld zone defects
 - 6.12.3 Process control plan
 - 6.13 Visual inspection of the drill-pipe weld zone
 - 6.13.1 General
 - 6.13.2 Disposition of defects
 - 6.14 Non-destructive examination of the weld zone
 - 6.14.1 General
 - 6.14.2 Wet fluorescent magnetic-particle inspection
 - 6.14.3 Ultrasonic inspection — Procedure
 - 6.14.4 Ultrasonic inspection — Reference standard
 - 6.14.5 Ultrasonic inspection — System capability records
 - 6.14.6 Disposition of defects
 - 6.15 Marking of drill-pipe
 - 6.15.1 General
 - 6.15.2 Drill-pipe marking
 - 6.15.3 Traceability marking
 - 6.15.4 Drill-pipe marking on the pipe body
 - 6.15.5 Drill-pipe marking on the tool joint
 - 6.16 Minimum facility requirements for drill-pipe manufacturers
 - 6.17 Documentation requirements of drill-pipe
 - 6.17.1 Standard documentation
 - 6.17.2 Supplementary documents
 - 6.17.3 Electronic data interchange
 - 6.17.4 Retention of records
- 7 Requirements for drill-pipe body
- 7.1 Information to be supplied when placing orders for drill-pipe bodies
 - 7.2 Dimensional and mass requirements

7.2.1	General
7.2.2	Configuration
7.2.3	Internal upset area
7.2.4	Outside-diameter tolerance
7.2.5	Inside diameter
7.2.6	Pipe-body wall thickness and tolerance
7.2.7	Length
7.2.8	Mass
7.2.9	Straightness
7.2.10	Upset and drill-pipe body alignment
7.2.11	Upset ovality
7.3	Material requirements
7.3.1	Chemical composition
7.3.2	Tensile requirements
7.3.3	Charpy V-notch absorbed-energy requirements — Grade E
7.3.4	Charpy V-notch absorbed-energy requirements — Grades X, G, S, D and F
7.3.5	Charpy V-notch absorbed-energy requirements — Alternative temperature
7.3.6	Surface hardness requirements
7.4	Process of manufacture
7.4.1	Processes requiring validation
7.4.2	General
7.4.3	Heat treatment
7.4.4	External coating
7.5	Traceability
7.6	Testing — General
7.6.1	Test-equipment calibration
7.6.2	Heat-treatment lot
7.7	Testing of chemical composition
7.7.1	Heat analysis
7.7.2	Product analysis
7.7.3	Test method
7.7.4	Re-test of product analysis
7.8	Tensile tests
7.8.1	Procedures
7.8.2	Test equipment calibration
7.8.3	Test specimens
7.8.4	Frequency of testing
7.8.5	Heat control test
7.8.6	Re-tests
7.8.7	Defective specimens
7.9	Charpy V-notch impact tests
7.9.1	Procedure
7.9.2	Specimen size and location
7.9.3	Frequency of testing
7.9.4	Heat control test
7.9.5	Re-test
7.9.6	Defective specimens
7.10	Drill-pipe-body wall thickness
7.11	Drill-pipe-body length
7.12	Internal upset
7.13	Internal profile
7.14	Straightness
7.15	Upset and drill-pipe body alignment
7.16	Mass determination
7.17	Imperfections and defects of drill-pipe body
7.17.1	General
7.17.2	Surface-breaking pipe-body defects
7.17.3	Surface-breaking upset defects
7.17.4	Elephant hide
7.17.5	Quench cracks
7.17.6	Process control plan
7.18	Visual inspection of drill-pipe body
7.18.1	General
7.18.2	Coverage

- 7.18.3 Disposition
- 7.18.4 Elephant hide
- 7.19 Non-destructive examination
- 7.19.1 General
- 7.19.2 Coverage
- 7.19.3 Applicable standards
- 7.19.4 Reference standards
- 7.19.5 Documented procedures
- 7.19.6 Inspection thresholds
- 7.19.7 Automated inspection-system signal evaluation
- 7.19.8 NDE system capability records
- 7.19.9 Evaluation of indications (prove-up)
- 7.19.10 Disposition of defects
- 7.20 Marking
- 7.20.1 General
- 7.20.2 Paint-stencilled marking sequence
- 7.21 Minimum facility requirements for drill-pipe-body manufacturer
- 7.22 Documentation requirements
- 7.22.1 Certificate of inspection
- 7.22.2 Tally list
- 7.22.3 Electronic data interchange
- 7.22.4 Retention of records

8 Requirements for tool joints

- 8.1 Information to be supplied when placing orders for tool joints
- 8.2 Dimensional requirements
- 8.2.1 General
- 8.2.2 Configuration
- 8.2.3 Tool-joint type
- 8.2.4 Dimensions
- 8.2.5 Rotary shouldered connection
- 8.3 Material requirements
- 8.3.1 Chemical composition
- 8.3.2 Tensile requirements
- 8.3.3 Hardness
- 8.3.3.1 Grades E, X, G and S
- 8.3.3.2 Grades D and F
- 8.3.4 Charpy V-notch absorbed energy requirements
- 8.4 Process of manufacture
- 8.4.1 Processes requiring validation
- 8.4.2 Material
- 8.4.3 Heat treatment
- 8.4.4 Threading
- 8.4.5 Surface treatment to minimize galling
- 8.4.6 Break-in procedure
- 8.4.7 Hard banding
- 8.4.8 Thread protection
- 8.5 Traceability
- 8.6 Testing — General
- 8.6.1 Test-equipment calibration
- 8.6.2 Heat-treatment lot
- 8.7 Testing of chemical composition
- 8.7.1 General
- 8.7.2 Product analyses
- 8.7.3 Test method
- 8.8 Tensile tests
- 8.8.1 Procedures
- 8.8.2 Test-equipment calibration
- 8.8.3 Test specimens
- 8.8.4 Frequency of test
- 8.8.5 Heat control tensile tests
- 8.8.6 Re-test
- 8.8.7 Defective specimens
- 8.9 Hardness tests

8.9.1	Procedure
8.9.2	Test specimen
8.9.3	Frequency of testing
8.9.4	Heat control hardness tests
8.9.5	Re-tests
8.10	Charpy V-notch impact tests
8.10.1	Procedures
8.10.2	Specimen size and location
8.10.3	Frequency of testing
8.10.4	Heat control test
8.10.5	Re-test
8.10.6	Defective specimens
8.11	Imperfections and defects
8.11.1	General
8.11.2	Surface breaking defects
8.11.3	Quench cracks
8.11.4	Process control plan
8.12	Non-destructive examination
8.12.1	General
8.12.2	Wet magnetic-particle inspection
8.12.3	Disposition of defects
8.13	Marking
8.13.1	General
8.13.2	Die stamp marking
8.14	Minimum facility requirements for tool-joint manufacturers
8.15	Documentation requirements for tool joints
8.15.1	Certificate of inspection
8.15.2	Electronic data interchange
8.15.3	Retention of records

Annex A (normative) Tables in SI units

Annex B (normative) Figures in SI (USC) units

Annex C (normative) Tables in USC units

Annex D (normative) Purchaser inspection

D.1	Inspection notice
D.2	Plant access
D.3	Compliance
D.4	Rejection

Annex E (informative) Supplementary requirements

E.1	General
E.2	SR2 drill-pipe-body for grades E, X, G, D and F
E.2.1	Defects, imperfections and NDE
E.2.2	Marking
E.3	SR15 drill-pipe — Test certificates
E.4	SR19 pipe body — Charpy V-notch impact toughness testing of grade E
E.4.1	Impact requirements
E.4.2	Frequency of testing
E.4.3	Marking
E.5	SR20 alternative low-temperature Charpy V-notch impact requirements
E.5.1	General
E.5.2	Alternative low temperature
E.5.3	Marking
E.6	SR23 weld zone — Lot size
E.7	SR24 Charpy V-notch — Increased weld-zone requirements
E.7.1	Requirements
E.7.2	Marking

Annex F (informative) Procedures used to convert from USC units to SI units for drill-pipe

F.1	Background
F.2	General

F.2.1	Rounding
F.2.2	Fractions
F.2.3	Tolerances
F.3	Pipe dimensions
F.3.1	Outside diameter
F.3.2	Wall thickness
F.3.3	Inside diameter
F.3.4	Diameters and lengths of upsets
F.4	Plain-end linear mass
F.5	Approximate linear mass
F.6	Tensile tests
F.6.1	Yield strength
F.6.2	Tensile strength
F.6.3	Elongation
F.7	Charpy impact energy
F.8	Temperature

Annex G (normative) Product specification levels

G.1	General
G.2	Additional requirements
G.3	Through-wall hardness testing of tool joints
G.3.1	Procedures
G.3.2	Hardness-test locations
G.3.3	Hardness re-tests
G.4	Markings

Page count: 108