

ISO 11961:2018 (E)

Petroleum and natural gas industries — Steel drill pipe

Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms, definitions, symbols and abbreviated terms
3.1	Terms and definitions
3.2	Symbols and abbreviated terms
4	Conformance
4.1	Dual citing of normative references
4.2	Units of measurement
5	Information to be supplied when placing orders for drill-pipe
5.1	Grades D95 and F105
5.2	General information
5.3	Additional information
6	Requirements for drill-pipe
6.1	General
6.2	Dimensions, masses and connections
6.2.1	Standard configuration
6.2.2	Alternative configurations
6.2.3	Drill-pipe weld neck diameters
6.2.4	Tool-joint inside diameters
6.2.5	Length
6.2.6	Length of tool-joint outside diameter
6.2.7	End-drift
6.2.8	Drill-pipe body and tool-joint alignment
6.2.9	Weld-zone profile
6.3	Material requirements
6.3.1	General
6.3.2	Weld-zone yield strength
6.3.3	Weld-zone hardness
6.3.3.1	Grades E, X, G and S
6.3.3.2	Grades D and F
6.3.4	Weld-zone Charpy V-notch absorbed-energy requirements
6.3.5	Weld-zone Charpy V-notch absorbed energy — Alternative requirements
6.3.6	Weld-zone transverse side bend properties
6.3.7	Sulfide stress cracking test — Grades D and F
6.3.7.1	85 % SMYS all parts (default)
6.3.7.2	Alternative testing (by agreement between purchaser and manufacturer)
6.4	Process of manufacture for drill-pipe
6.4.1	Processes requiring validation
6.4.2	Welding qualification
6.4.3	Welding of tool joints to drill-pipe body and post-weld heat treatment
6.4.4	Weld machining
6.4.5	Internal coating
6.4.6	External coating
6.4.7	Thread protection
6.5	Traceability
6.6	Testing — General

- 6.6.1 Test equipment calibration
- 6.6.2 Dimensional inspection
- 6.6.3 Drill-pipe length
- 6.6.4 Straightness
- 6.6.5 End-drift test
- 6.6.6 Internal profile
- 6.6.7 Drill-pipe body and tool-joint alignment
- 6.7 Testing of welds
 - 6.7.1 Lot size
 - 6.7.2 Test specimens
- 6.8 Tensile test
 - 6.8.1 Procedures
 - 6.8.2 Test equipment calibration
 - 6.8.3 Specimens
 - 6.8.4 Frequency
 - 6.8.5 Defective specimen
 - 6.8.6 Re-tests
- 6.9 Hardness test
 - 6.9.1 Procedures
 - 6.9.2 Surface hardness test
 - 6.9.3 Surface hardness — Re-test
 - 6.9.4 Through-wall hardness test
 - 6.9.5 Through-wall hardness — Re-tests
- 6.10 Charpy V-notch impact test
 - 6.10.1 Procedures
 - 6.10.2 Specimen size and orientation
 - 6.10.3 Test frequency
 - 6.10.4 Re-tests
 - 6.10.5 Defective specimens
- 6.11 Transverse side-bend test
 - 6.11.1 Procedure
 - 6.11.2 Specimens
 - 6.11.3 Test frequency
 - 6.11.4 Re-tests
- 6.12 Imperfections and defects in drill-pipe
 - 6.12.1 General
 - 6.12.2 Weld zone defects
 - 6.12.3 Process control plan
- 6.13 Visual inspection of the drill-pipe weld zone
 - 6.13.1 General
 - 6.13.2 Disposition of defects
- 6.14 Non-destructive examination of the weld zone
 - 6.14.1 General
 - 6.14.2 Wet fluorescent magnetic-particle inspection
 - 6.14.3 Ultrasonic inspection — Procedure
 - 6.14.4 Ultrasonic inspection — Reference standard
 - 6.14.5 Ultrasonic inspection — System capability records
 - 6.14.6 Disposition of defects
- 6.15 Marking of drill-pipe
 - 6.15.1 General
 - 6.15.2 Drill-pipe marking
 - 6.15.3 Traceability marking
 - 6.15.4 Drill-pipe marking on the pipe body
 - 6.15.5 Drill-pipe marking on the tool joint
- 6.16 Minimum facility requirements for drill-pipe manufacturers
- 6.17 Documentation requirements of drill-pipe
 - 6.17.1 Standard documentation
 - 6.17.2 Supplementary documents
 - 6.17.3 Electronic data interchange
 - 6.17.4 Retention of records
- 7 Requirements for drill-pipe body
 - 7.1 Information to be supplied when placing orders for drill-pipe bodies
 - 7.2 Dimensional and mass requirements

7.2.1	General
7.2.2	Configuration
7.2.3	Internal upset area
7.2.4	Outside-diameter tolerance
7.2.5	Inside diameter
7.2.6	Pipe-body wall thickness and tolerance
7.2.7	Length
7.2.8	Mass
7.2.9	Straightness
7.2.10	Upset and drill-pipe body alignment
7.2.11	Upset ovality
7.3	Material requirements
7.3.1	Chemical composition
7.3.2	Tensile requirements
7.3.3	Charpy V-notch absorbed-energy requirements — Grade E
7.3.4	Charpy V-notch absorbed-energy requirements — Grades X, G, S, D and F
7.3.5	Charpy V-notch absorbed-energy requirements — Alternative temperature
7.3.6	Surface hardness requirements
7.4	Process of manufacture
7.4.1	Processes requiring validation
7.4.2	General
7.4.3	Heat treatment
7.4.4	External coating
7.5	Traceability
7.6	Testing — General
7.6.1	Test-equipment calibration
7.6.2	Heat-treatment lot
7.7	Testing of chemical composition
7.7.1	Heat analysis
7.7.2	Product analysis
7.7.3	Test method
7.7.4	Re-test of product analysis
7.8	Tensile tests
7.8.1	Procedures
7.8.2	Test equipment calibration
7.8.3	Test specimens
7.8.4	Frequency of testing
7.8.5	Heat control test
7.8.6	Re-tests
7.8.7	Defective specimens
7.9	Charpy V-notch impact tests
7.9.1	Procedure
7.9.2	Specimen size and location
7.9.3	Frequency of testing
7.9.4	Heat control test
7.9.5	Re-test
7.9.6	Defective specimens
7.10	Drill-pipe-body wall thickness
7.11	Drill-pipe-body length
7.12	Internal upset
7.13	Internal profile
7.14	Straightness
7.15	Upset and drill-pipe body alignment
7.16	Mass determination
7.17	Imperfections and defects of drill-pipe body
7.17.1	General
7.17.2	Surface-breaking pipe-body defects
7.17.3	Surface-breaking upset defects
7.17.4	Elephant hide
7.17.5	Quench cracks
7.17.6	Process control plan
7.18	Visual inspection of drill-pipe body
7.18.1	General
7.18.2	Coverage

- 7.18.3 Disposition
- 7.18.4 Elephant hide
- 7.19 Non-destructive examination
 - 7.19.1 General
 - 7.19.2 Coverage
 - 7.19.3 Applicable standards
 - 7.19.4 Reference standards
 - 7.19.5 Documented procedures
 - 7.19.6 Inspection thresholds
 - 7.19.7 Automated inspection-system signal evaluation
 - 7.19.8 NDE system capability records
 - 7.19.9 Evaluation of indications (prove-up)
 - 7.19.10 Disposition of defects
- 7.20 Marking
 - 7.20.1 General
 - 7.20.2 Paint-stencilled marking sequence
- 7.21 Minimum facility requirements for drill-pipe-body manufacturer
- 7.22 Documentation requirements
 - 7.22.1 Certificate of inspection
 - 7.22.2 Tally list
 - 7.22.3 Electronic data interchange
 - 7.22.4 Retention of records

8 Requirements for tool joints

- 8.1 Information to be supplied when placing orders for tool joints
- 8.2 Dimensional requirements
 - 8.2.1 General
 - 8.2.2 Configuration
 - 8.2.3 Tool-joint type
 - 8.2.4 Dimensions
 - 8.2.5 Rotary shouldered connection
- 8.3 Material requirements
 - 8.3.1 Chemical composition
 - 8.3.2 Tensile requirements
 - 8.3.3 Hardness
 - 8.3.3.1 Grades E, X, G and S
 - 8.3.3.2 Grades D and F
 - 8.3.4 Charpy V-notch absorbed energy requirements
- 8.4 Process of manufacture
 - 8.4.1 Processes requiring validation
 - 8.4.2 Material
 - 8.4.3 Heat treatment
 - 8.4.4 Threading
 - 8.4.5 Surface treatment to minimize galling
 - 8.4.6 Break-in procedure
 - 8.4.7 Hard banding
 - 8.4.8 Thread protection
- 8.5 Traceability
- 8.6 Testing — General
 - 8.6.1 Test-equipment calibration
 - 8.6.2 Heat-treatment lot
- 8.7 Testing of chemical composition
 - 8.7.1 General
 - 8.7.2 Product analyses
 - 8.7.3 Test method
- 8.8 Tensile tests
 - 8.8.1 Procedures
 - 8.8.2 Test-equipment calibration
 - 8.8.3 Test specimens
 - 8.8.4 Frequency of test
 - 8.8.5 Heat control tensile tests
 - 8.8.6 Re-test
 - 8.8.7 Defective specimens
- 8.9 Hardness tests

- 8.9.1 Procedure
- 8.9.2 Test specimen
- 8.9.3 Frequency of testing
- 8.9.4 Heat control hardness tests
- 8.9.5 Re-tests
- 8.10 Charpy V-notch impact tests
- 8.10.1 Procedures
- 8.10.2 Specimen size and location
- 8.10.3 Frequency of testing
- 8.10.4 Heat control test
- 8.10.5 Re-test
- 8.10.6 Defective specimens
- 8.11 Imperfections and defects
- 8.11.1 General
- 8.11.2 Surface breaking defects
- 8.11.3 Quench cracks
- 8.11.4 Process control plan
- 8.12 Non-destructive examination
- 8.12.1 General
- 8.12.2 Wet magnetic-particle inspection
- 8.12.3 Disposition of defects
- 8.13 Marking
- 8.13.1 General
- 8.13.2 Die stamp marking
- 8.14 Minimum facility requirements for tool-joint manufacturers
- 8.15 Documentation requirements for tool joints
- 8.15.1 Certificate of inspection
- 8.15.2 Electronic data interchange
- 8.15.3 Retention of records

Annex A (normative) Tables in SI units

Annex B (normative) Figures in SI (USC) units

Annex C (normative) Tables in USC units

Annex D (normative) Purchaser inspection

- D.1 Inspection notice
- D.2 Plant access
- D.3 Compliance
- D.4 Rejection

Annex E (informative) Supplementary requirements

- E.1 General
- E.2 SR2 drill-pipe-body for grades E, X, G, D and F
- E.2.1 Defects, imperfections and NDE
- E.2.2 Marking
- E.3 SR15 drill-pipe — Test certificates
- E.4 SR19 pipe body — Charpy V-notch impact toughness testing of grade E
- E.4.1 Impact requirements
- E.4.2 Frequency of testing
- E.4.3 Marking
- E.5 SR20 alternative low-temperature Charpy V-notch impact requirements
- E.5.1 General
- E.5.2 Alternative low temperature
- E.5.3 Marking
- E.6 SR23 weld zone — Lot size
- E.7 SR24 Charpy V-notch — Increased weld-zone requirements
- E.7.1 Requirements
- E.7.2 Marking

Annex F (informative) Procedures used to convert from USC units to SI units for drill-pipe

- F.1 Background
- F.2 General

- F.2.1 Rounding
- F.2.2 Fractions
- F.2.3 Tolerances
- F.3 Pipe dimensions
 - F.3.1 Outside diameter
 - F.3.2 Wall thickness
 - F.3.3 Inside diameter
 - F.3.4 Diameters and lengths of upsets
- F.4 Plain-end linear mass
- F.5 Approximate linear mass
- F.6 Tensile tests
 - F.6.1 Yield strength
 - F.6.2 Tensile strength
 - F.6.3 Elongation
- F.7 Charpy impact energy
- F.8 Temperature

Annex G (normative) Product specification levels

- G.1 General
- G.2 Additional requirements
- G.3 Through-wall hardness testing of tool joints
 - G.3.1 Procedures
 - G.3.2 Hardness-test locations
 - G.3.3 Hardness re-tests
- G.4 Markings

Page count: 108