

DIN EN ISO 19901-9:2019-12 (E)

Petroleum and natural gas industries - Specific requirements for offshore structures - Part 9: Structural integrity management (ISO 19901-9:2019); English version EN ISO 19901-9:2019

Contents

| | Page |
|--|-----------|
| Foreword | vi |
| Introduction | vii |
| 1 Scope | 1 |
| 2 Normative references | 1 |
| 3 Terms and definitions | 2 |
| 4 Symbols | 4 |
| 5 Abbreviated terms | 5 |
| 6 SIM fundamentals | 6 |
| 6.1 General | 6 |
| 6.2 Limit states and performance levels | 6 |
| 6.3 Fitness-for-service assessment | 6 |
| 6.4 Management framework | 7 |
| 6.5 Design | 8 |
| 6.6 Topsides | 9 |
| 6.7 Continued service | 9 |
| 6.8 Structural integrity interfaces | 9 |
| 7 SIM process | 9 |
| 8 SIM data | 10 |
| 8.1 General | 10 |
| 8.2 Missing data | 11 |
| 8.3 Data management | 11 |
| 9 SIM evaluation | 12 |
| 9.1 General | 12 |
| 9.2 Data evaluation | 12 |
| 9.3 Hazards, hazardous events and degradation mechanisms | 12 |
| 9.4 Critical structure (CS) | 12 |
| 9.5 Risk | 12 |
| 9.5.1 General | 12 |
| 9.5.2 Consequence | 13 |
| 9.5.3 Likelihood | 13 |
| 9.5.4 Risk presentation | 13 |
| 9.6 Demonstrating fitness-for-service | 13 |
| 9.7 Assessment | 14 |
| 9.7.1 General | 14 |
| 9.7.2 Assessment motive | 14 |
| 9.7.3 Assessment initiators | 15 |
| 9.8 Mitigation measures | 15 |
| 9.8.1 General | 15 |
| 9.8.2 Consequence reduction | 16 |
| 9.8.3 Likelihood reduction | 16 |

| | | |
|-----------|--|-----------|
| 10 | SIM strategy | 16 |
| 10.1 | General..... | 16 |
| 10.2 | Inspection strategy..... | 17 |
| 10.2.1 | General..... | 17 |
| 10.2.2 | Inspection motives..... | 18 |
| 10.2.3 | Inspection type..... | 18 |
| 10.2.4 | Inspection method..... | 18 |
| 10.2.5 | Inspection interval..... | 18 |
| 10.2.6 | Inspection scope..... | 20 |
| 10.2.7 | Pre-selected inspection areas..... | 20 |
| 10.3 | Maintenance strategy..... | 21 |
| 10.4 | Monitoring strategy..... | 21 |
| 10.4.1 | General..... | 21 |
| 10.4.2 | Weight and centre of gravity (CoG) monitoring..... | 22 |
| 10.4.3 | Deck elevation monitoring..... | 22 |
| 10.4.4 | Natural frequency monitoring..... | 22 |
| 10.4.5 | Corrosion protection monitoring..... | 22 |
| 10.4.6 | Metoccean monitoring..... | 22 |
| 10.5 | Evacuation strategy..... | 22 |
| 10.6 | Marine site investigations..... | 23 |
| 11 | SIM Program | 23 |
| 11.1 | General..... | 23 |
| 11.2 | Inspection program..... | 23 |
| 11.2.1 | General..... | 23 |
| 11.2.2 | Specifications..... | 23 |
| 11.2.3 | Inspection method..... | 24 |
| 11.3 | Maintenance program..... | 25 |
| 11.4 | Monitoring program..... | 25 |
| 12 | Assessment | 26 |
| 12.1 | General..... | 26 |
| 12.2 | Assessment information..... | 26 |
| 12.3 | Assessment method..... | 26 |
| 12.3.1 | General..... | 26 |
| 12.3.2 | Qualitative method..... | 27 |
| 12.3.3 | Semi-quantitative method..... | 28 |
| 12.3.4 | Quantitative methods..... | 29 |
| 12.3.5 | Fatigue analysis..... | 31 |
| 12.4 | Assessment model..... | 31 |
| 12.4.1 | General..... | 31 |
| 12.4.2 | Tubular members..... | 31 |
| 12.4.3 | Connections..... | 32 |
| 12.4.4 | Conductors..... | 32 |
| 12.4.5 | Damage..... | 32 |
| 12.4.6 | Repaired and strengthened elements..... | 33 |
| 12.4.7 | Foundation model..... | 33 |
| 12.4.8 | Material strength..... | 34 |
| 12.5 | Assessment for gravity hazard..... | 34 |
| 12.5.1 | General..... | 34 |
| 12.5.2 | Design level method (DLM)..... | 35 |
| 12.5.3 | Ultimate strength method (USM)..... | 35 |
| 12.6 | Assessment for metoccean hazard..... | 35 |
| 12.6.1 | General..... | 35 |
| 12.6.2 | Metoccean criteria..... | 35 |
| 12.6.3 | Crest elevation..... | 35 |
| 12.6.4 | Metoccean action combinations — Jacket..... | 36 |
| 12.6.5 | Metoccean action combinations — Deck..... | 36 |

| | | |
|--|--|------------|
| 12.6.6 | Directionality of metocean hazards | 36 |
| 12.6.7 | Design level method (DLM) | 37 |
| 12.6.8 | Linear-elastic redundancy method | 37 |
| 12.6.9 | Ultimate strength method (USM) | 37 |
| 12.7 | Assessment for seismic hazard | 38 |
| 12.7.1 | General | 38 |
| 12.7.2 | Seismic criteria | 38 |
| 12.7.3 | Seismic action combinations | 38 |
| 12.7.4 | Directionality of seismic hazards | 39 |
| 12.7.5 | Design level method (DLM) | 39 |
| 12.7.6 | Ultimate strength method (USM) | 40 |
| 12.8 | Assessment for collision hazard | 40 |
| 12.8.1 | General | 40 |
| 12.8.2 | Collision zone | 41 |
| 12.8.3 | Collision criteria | 41 |
| 12.8.4 | Directionality of collision hazards | 41 |
| 12.8.5 | Collision assessment method | 41 |
| 12.9 | Assessment for ice hazard | 41 |
| 12.10 | Assessment for explosion hazard | 42 |
| 12.11 | Assessment for fire hazard | 42 |
| 13 | Reuse | 42 |
| 13.1 | General | 42 |
| 13.2 | Fatigue in reused structures | 42 |
| 13.3 | Steel in reused structures | 42 |
| 13.4 | Inspection of reused structures | 43 |
| 13.4.1 | General | 43 |
| 13.4.2 | Initial condition assessment of structural members and connections | 43 |
| 13.4.3 | Extent of weld inspection | 43 |
| 13.4.4 | Corrosion protection systems | 44 |
| 13.5 | Removal and reinstallation | 44 |
| 14 | Decommissioning and removal | 44 |
| 14.1 | General | 44 |
| 14.2 | Decommissioning process | 44 |
| 14.3 | Pre-decommissioning data gathering | 44 |
| 14.4 | Planning and engineering | 44 |
| 14.5 | Well decommissioning | 45 |
| 14.6 | Facilities decommissioning | 45 |
| 14.7 | Pipeline decommissioning | 45 |
| 14.8 | Conductor removal | 45 |
| 14.9 | Structure removal | 45 |
| 14.10 | Site clearance | 45 |
| Annex A (informative) Additional information and guidance | | 46 |
| Bibliography | | 141 |