ISO 11960:2020-03 (E)

Petroleum and natural gas industrie s - Steel pipes for use as casing or tubing for wells

Contents

Page

Foreword ..... **x**

Introduction ..... **xi**

1 Scope **1**

2 Normative references **1**

3 Terms, definitions, symbols and abbreviated terms **3**
3.1 Terms and definitions 3
3.2 Symbols and abbreviated terms 7

4 Conformance **8**
4.1 Dual referencing of normative references 8
4.2 Units of measurement 9

5 Information to be supplied by the purchaser **9**
5.1 Grades C90, T95 and C110 9
5.2 Casing 9
5.3 Tubing 11
5.4 Coupling stock, coupling material and accessory material 13

6 Process of manufacture **14**
6.1 General 14
6.2 Heat treatment 14
6.2.1 General 14
6.2.2 Grades J55, K55, N80 all types and R95 15
6.2.3 Grades L80 all types, C90, T95 and C110 15
6.3 Straightening 15
6.3.1 Grades H40, J55, K55, N80 all types 15
6.3.2 Grades R95 and P110 15
6.3.3 Grade L80 15
6.3.4 Grades C90, T95 and C110 16
6.3.5 Grade Q125 16
6.4 Traceability 16
6.4.1 General 16
6.4.2 Serialization of Grades C90, T95, C110 and Q125 16
6.5 Processes requiring validation 16

7 Material requirements **17**
7.1 Chemical composition 17
7.2 Tensile properties 17
7.2.1 General 17
7.2.2 Elongation 17
7.2.3 Yield strength 17
7.2.4 Statistical tensile testing — Grades C90, T95 and C110 18
7.3 Charpy V-notch test — General requirements 18
7.3.1 Evaluation of test results 18
7.3.2 Critical thickness 18
7.3.3 Specimen size and orientation 18
7.3.4 Hierarchy of test specimens 18
7.3.5 Alternative size impact test specimens 19
7.3.6 Sub-size test specimens 19
7.3.7 Test temperature 19
7.3.8 Statistical impact testing 19
7.3.9 Reference information 19

7.4 Charpy V-notch — Absorbed energy requirements for coupling stock, coupling material, coupling blanks and couplings 19
7.4.1 General 19
7.4.2 Grade H40 19
7.4.3 Grades J55 and K55 for API threads 19
7.4.4 Grades N80 all Types, R95, L80 all Types, C90, T95, P110 and Q125 for API threads 20
7.4.5 Special end-finish 20
7.5 Charpy V-notch — Absorbed energy requirements for pipe 20
7.5.1 Grades H40, J55 and K55 20
7.5.2 Grades N80 all Types, R95, L80, C90, T95 and P110 20
7.5.3 Grades C110 and Q125 21
7.5.4 Test specimen 21
7.5.5 Testing conditions 22
7.6 Charpy V-notch — Absorbed energy requirements for accessory material 22
7.6.1 Accessory material — General 22
7.6.2 Accessory material for accessories with internal API threads except integral tubing connections 22
7.6.3 Accessory material for accessories with internal special end-finish tapered interference-type threads 22
7.6.4 Accessory material for accessories with external threads 22
7.6.5 Accessory material for accessories with either integral tubing connections or internal special end-finish connections that do not have thread interference 22
7.6.6 Critical thickness for accessory material and special end-finish material 22
7.7 Maximum hardness 23
7.7.1 Grades L80 all types, C90, T95 and C110 23
7.7.2 Grade Q125 — All products 23
7.8 Hardness variation — Grades C90, T95, C110 and Q125 23
7.9 Process control — Grades C90, T95, C110 and Q125 23
7.10 Hardenability — Minimum percentage martensite for quenched and tempered products 24
7.10.1 Grade L80 Type 1 24
7.10.2 Grades C90 and T95 24
7.10.3 Grade C110 24
7.10.4 All grades except Grades L80, C90, T95 and C110 24
7.11 Grain size — Grades C90, T95 and C110 25
7.12 Surface condition — Grade L80 13Cr 25
7.13 Flattening — Electric-welded pipe 25
7.14 Sulfide stress cracking test — Grades C90, T95 and C110 25
7.14.1 General guidance 25
7.14.2 Test and retest requirements and recommendations 25
7.14.3 Test sample selection and location 26
7.14.4 Test solution 26
7.14.5 Minimum SSC requirements 27
7.14.6 Invalidation of tests 28
7.14.7 Additional testing provisions for ANSI/NACE TM0177-2016 Method D 28

8 Dimensions, masses, tolerances, product ends and defects 28
8.1 Labels and sizes 28
8.2 Dimensions and masses 28
8.3 Diameter 29
8.3.1 Measurement and design 29
8.3.2 Requirements 29
8.4 Wall thickness 29
8.5 Mass 29
8.6 Length 30
8.7 Casing jointers 30
8.8 Height and trim of electric-weld flash 30
8.8.1 Trimming electric-weld flash 30
8.8.2 Grades H40, J55, K55, N80 all types, R95; and L80 Type 1 30
8.8.3 Grades P110 and Q125 31
8.8.4 Disposition 31
8.9 Straightness 31

8.9.1 Pipe 31
8.9.2 Coupling stock, coupling material and accessory material 31
8.10 Drift requirements 31
8.11 Tolerances on dimensions and masses 32
8.11.1 Outside diameter 32
8.11.2 Wall thickness 32
8.11.3 Mass 32
8.11.4 Inside diameter 33
8.11.5 Upset dimensions 33
8.11.6 Extended length upsets 33
8.12 Product ends 33
8.12.1 Plain-end pipe 33
8.12.2 Product with API threads 33
8.12.3 Rounded nose 33
8.12.4 Threading 33
8.12.5 Special end finish 34
8.13 Defects 34
8.13.1 Pipe and accessory made from pipe 34
8.13.2 Accessory material not made from pipe, coupling stock and coupling material 34
8.13.3 Process control plan 35
8.14 Coupling make-up and thread protection 35
8.14.1 All Grades except Q125 35
8.14.2 Grade Q125 35

9 Couplings 35
9.1 General requirements 35
9.2 Alternative grades or heat treatments 36
9.3 Mechanical properties 36
9.4 Dimensions and tolerances 36
9.4.1 All Grades except Q125 36
9.4.2 Grade Q125 37
9.5 Regular couplings 37
9.6 Special-clearance couplings — All Grades except Q125 37
9.7 Combination couplings 37
9.8 Seal-ring couplings 37
9.9 Special-bevel tubing regular couplings — All Grades 37
9.10 Threading — Couplings 38
9.11 Surface inspection 38
9.12 Measurement of imperfections 38
9.13 Repair and removal of imperfections and defects 39
9.14 Thread surface treatment — Grade Q125 39
9.15 Couplings and coupling blank protection — Grades C90, T95, C110 and Q125 39

10 Inspection and testing 39
10.1 Test equipment 39
10.2 Lot definition for testing of mechanical properties 39
10.2.1 Grades H40, J55, K55, N80 all types, L80 Type 1, R95 and P110 — Coupling stock, coupling material and pipe (except pup joints heat-treated after cutting to blank or individual length) 39
10.2.2 Grades L80 13Cr, C90, T95, C110 and Q125 — Coupling stock, coupling material and pipe (except pup joints heat-treated after cutting to blank or individual length) 39
10.2.3 Coupling blanks, pup joints or accessory material heat-treated after cutting to blank or individual length 40
10.3 Testing of chemical composition 40
10.3.1 Heat analyses 40
10.3.2 Product analyses 40
10.3.3 Test method 40
10.3.4 Recheck of product analyses — All Grades 41

10.4 Tensile tests 41
10.4.1 Stress-relief temperature — All grades 41
10.4.2 Heat-control tensile tests — All Grades except Q125 41
10.4.3 Frequency of testing and location of test specimen — Casing and tubing 41
10.4.4 Frequency of testing and test specimen location — Coupling stock, coupling material, coupling blanks, pup joints and accessory material 41
10.4.5 Test specimens — General 42
10.4.6 Test specimens — Additional requirements for coupling blanks, coupling stock coupling material and pup joint and accessory materials — Grades C110 and Q125 42
10.4.7 Test method 42
10.4.8 Invalidation of tests 43
10.4.9 Retests — All products (except coupling blanks, coupling stock, coupling material, pup joints or accessory material) — Grades C90, T95, C110 and Q125 43
10.4.10 Retests — Coupling blanks, coupling stock, coupling material, pup joints or accessory material in Grades C90, T95, C110 and Q125 43
10.5 Flattening test 43
10.5.1 General requirement for testing 43
10.5.2 Frequency of testing 43
10.5.3 Test specimens 44
10.5.4 Test method for Grades H40, J55, K55, N80 all types, R95, and L80 Type 1 44
10.5.5 Test method for Grade P110 pipe and Grade Q125 casing 44
10.5.6 Invalidation of tests 44
10.5.7 Retests 44
10.6 Hardness test 44
10.6.1 Frequency of testing — General 44
10.6.2 Frequency of testing — Heat-control tests — Grade L80 45
10.6.3 Frequency of testing — Grade L80 45
10.6.4 Frequency of testing and test specimen location — Non-upset pipe — Grades C90, T95 and C110 45
10.6.5 Frequency of testing and test specimen location — Upset pipe — Grades C90 and T95 45
10.6.6 Frequency of testing and test specimen location — Coupling blanks, coupling stock, coupling material, pup joints and accessory material — Grades C90, T95 and C110 45
10.6.7 Frequency of testing — Grade Q125 46
10.6.8 Test specimens 46
10.6.9 Test method 46
10.6.10 Invalidation of tests 48
10.6.11 Periodic checks of hardness-testing machines 48
10.6.12 Verification of hardness-testing machines and indenters 48
10.6.13 Retests — Grade L80 49
10.6.14 Retests — Grades C90, T95 and C110 products except for coupling blanks, pup joints or accessory material heat-treated after cutting to individual lengths 49
10.6.15 Retests — Grades C90, T95 and C110 coupling blanks, pup joints or accessory material heat-treated after cutting to individual lengths 50
10.6.16 Retests — Grade Q125 — General 50
10.6.17 Retests — Grade Q125 — Casing, coupling stock and coupling material 50
10.6.18 Retests — Grade Q125 — Coupling blanks, pup joints and accessory material 50
10.6.19 Rejected lots — Grades L80 all types, C90, T95, C110 and Q125 50
10.7 Impact test 50
10.7.1 Sampling —Grades J55 and K55 50
10.7.2 Sampling — Grades N80 all types, R95, L80, C90, T95, C110 and P110 50
10.7.3 Sampling and test specimen location — Grade Q125 51
10.7.4 Test specimens 51
10.7.5 Test method 51

10.7.6 Invalidation of tests 51
10.7.7 Retest of a length — All Grades 51
10.7.8 Replacement of a reject length — All Grades 52
10.7.9 Multiple length rejection — Grade Q125 52
10.8 Grain size determination — Grades C90, T95 and C110 52
10.8.1 Sampling 52
10.8.2 Test method 52
10.9 Hardenability — Grades C90, T95 and C110 52
10.10 Sulfide stress-cracking test — Grades C90, T95 and C110 52
10.11 Metallographic evaluation — All EW Grades 52
10.12 Hydrostatic tests 53
10.12.1 Hydrostatic test procedures 53
10.12.2 Hydrostatic test requirements 53
10.12.3 Test pressure calculation 54
10.13 Dimensional testing 55
10.13.1 General 55
10.13.2 Diameter measurement 55
10.13.3 Diameter retests 55
10.13.4 Wall thickness measurement 56
10.13.5 Drift test 56
10.13.6 Length measurement 56
10.13.7 Mass (weight) determination 56
10.13.8 Straightness evaluation 57
10.13.9 Internal upset inspection 57
10.14 Visual inspection 57
10.14.1 General 57
10.14.2 Pipe body, coupling stock and coupling material (excluding pipe ends) 58
10.14.3 Pipe ends 58
10.14.4 Disposition 58
10.15 Non-destructive examination (NDE) 58
10.15.1 General 58
10.15.2 NDE personnel 59
10.15.3 Reference standards 59
10.15.4 NDE system capability records 59
10.15.5 Pipe body or coupling stock inspection — General 60
10.15.6 Full-body, full-length NDE of casing and tubing — Grades H40, J55, K55, N80 all types, L80 and R95 60
10.15.7 Full-body, full-length NDE of casing and tubing — Grade P110 to A.8 SR16 60
10.15.8 Full-body, full-length NDE of casing and tubing — Grade P110 and Grade P110 to A.8 SR16 and A.2 SR2 61
10.15.9 Full-body, full-length NDE of casing and tubing — Grades L80 13Cr, C90, T95, C110 and Q125 61
10.15.10 NDE of the weld seam of welded pipe 61
10.15.11 NDE of coupling stock, accessory material (except Grades L80 13Cr, C90, T95, C110 and Q125) and pup joints 62
10.15.12 NDE of coupling stock and accessory material – Grades L80 13Cr, C90, T95, C110 and Q125 62
10.15.13 NDE of coupling stock and accessory material — Grades C90 and T95 63
10.15.14 Untested pipe ends, coupling stock ends and accessory material ends 64
10.15.15 Pipe upsets 64
10.15.16 Pipe, coupling stock and accessory material requiring further evaluation 64

10.15.17 .....
Evaluation of indications (prove-up) 65
10.15.18 .....
Disposition of pipe containing defects 65
10.15.19 .....
Disposition of coupling stock and accessory material containing defects 66

11 Marking 67
11.1 General 67
11.2 Stamp marking requirements 68
11.2.1 Methods 68
11.2.2 Size 68
11.2.3 Location 68
11.2.4 Grades H40, J55, K55, N80 all types and P110 68
11.2.5 Grades R95, L80 all types, C90, T95, C110 and Q125 68
11.2.6 Make-up triangle marking 69
11.3 Stencil marking requirements 69
11.4 Colour identification 69
11.4.1 Colour coding 69
11.4.2 Product 1,8 m (6 ft) and longer 69
11.4.3 Loose couplings 70
11.4.4 Special-clearance couplings 70
11.4.5 Pup joints shorter than 1,8 m (6 ft) in length 70
11.4.6 Grade colour-codes 70
11.5 Thread and end-finish marking 70
11.5.1 API thread marking 70
11.5.2 Plain-end and special end-finish markings 70
11.6 Pipe-threader marking requirements 70

12 Coating and protection 71
12.1 Coatings 71
12.1.1 Coatings for protection during transit 71
12.1.2 Coatings for long-term storage 71
12.2 Thread protectors 72
12.2.1 General 72
12.2.2 Grade L80 13Cr 72
12.2.3 Driftable thread protectors 72

13 Documents 72
13.1 Electronic media 72
13.2 Certification requirements 72
13.3 Content of the certificate 72
13.4 Retention of records 74

14 Minimum facility requirements for various categories of manufacturer 74
14.1 Pipe mill 74
14.2 Processor 74
14.3 Pipe threader 74
14.4 Coupling, pup-joint or accessory manufacturer 75

Annex A (normative) **Supplementary requirements 76**
Annex B (normative) **Purchaser inspection 91**
Annex C (normative) **Tables in SI units 92**
Annex D (normative) **Figures in SI (USC) units 159**
Annex E (normative) **Tables in USC units 182**
Annex F (informative) **Procedures used to convert from USC units to SI units 248**
Annex G (normative) **Requirements for thread protector design validation 260**
Annex H (normative) **High collapse requirements 265**
Bibliography 267