

DIN EN ISO 23936-4:2025-02 (E)

Oil and gas industries including lower carbon energy - Non-metallic materials in contact with media related to oil and gas production - Part 4: Fiber-reinforced composite materials (ISO 23936-4:2024); English version EN ISO 23936-4:2024

| Contents | | Page |
|-----------------|---|-------------|
| Foreword | | v |
| Introduction | | vi |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions and abbreviated terms | 3 |
| 3.1 | Terms and definitions | 3 |
| 3.2 | Abbreviated terms | 4 |
| 4 | Technical requirements | 5 |
| 4.1 | General requirements | 5 |
| 4.2 | Cautionary remarks | 7 |
| 4.3 | Traceability | 7 |
| 4.4 | Test specimen identification | 7 |
| 4.5 | Validation of conformity | 9 |
| 4.6 | Quality control for fabrication of laminated test plates | 10 |
| 4.6.1 | General | 10 |
| 4.6.2 | Quality control for fabrication of plates | 10 |
| 4.7 | Test specimen preparation, quality control and identification | 12 |
| 4.7.1 | Preparation of test specimens | 12 |
| 4.7.2 | Quality control of specimen preparation | 12 |
| 5 | Level 1 – Material property characterization | 12 |
| 5.1 | General | 12 |
| 5.2 | Reporting | 14 |
| 6 | Level 2 - Material stability (short-term) | 14 |
| 6.1 | General | 14 |
| 6.2 | Test criteria | 14 |
| 6.2.1 | General | 14 |
| 6.2.2 | Exposure temperature | 15 |
| 6.2.3 | Exposure durations | 15 |
| 6.2.4 | Test fluids | 15 |
| 6.2.5 | Property test methods | 15 |
| 6.2.6 | Threshold criteria | 15 |
| 6.3 | Preconditioning considerations | 16 |
| 6.4 | Reporting | 16 |
| 7 | Level 3 – Material stability (accelerated) | 16 |
| 7.1 | General | 16 |
| 7.2 | Exposure temperatures | 17 |
| 7.3 | Exposure durations | 17 |
| 7.4 | Exposure fluids | 18 |
| 7.5 | Initial swelling | 18 |
| 7.6 | Property test methods | 18 |
| 7.7 | Threshold criteria | 18 |
| 7.8 | Preconditioning considerations | 18 |
| 7.9 | Evaluation of data for Level 3 | 19 |
| 7.10 | Reporting | 19 |

| | | |
|---------------------|---|-----------|
| 8 | Level 4 – Material stability (long-term) | 20 |
| 8.1 | General requirements for Level 4 evaluation..... | 20 |
| 8.2 | Exposure temperatures..... | 20 |
| 8.3 | Exposure durations..... | 20 |
| 8.4 | Exposure fluids..... | 20 |
| 8.5 | Initial swelling..... | 20 |
| 8.6 | Property test methods..... | 20 |
| 8.7 | Guidance for selection of Level 4 test methods..... | 21 |
| 8.8 | Preconditioning considerations..... | 21 |
| 8.9 | Evaluation of data for Level 4..... | 21 |
| 8.10 | Threshold baseline..... | 21 |
| 8.11 | Threshold criteria for composites..... | 22 |
| Annex A | (normative) Test media, conditions, equipment and procedures for ageing of composite materials | 23 |
| Annex B | (normative) Fabrication of laminated plates | 40 |
| Annex C | (normative) Specimen extraction from laminated plates | 45 |
| Annex D | (normative) Quality control and documentation of laminate and thermoplastic UD-tape | 49 |
| Annex E | (informative) Considerations for short-term thermomechanical evaluation and qualification | 53 |
| Annex F | (informative) Selecting elevated temperatures for accelerated tests | 54 |
| Bibliography | | 56 |