

DIN EN ISO 13680:2025-12 (E)

Oil and gas industries including lower carbon energy - Corrosion-resistant alloy seamless products for use as casing, tubing, coupling stock and accessory material - Technical delivery conditions (ISO 13680:2024); English version EN ISO 13680:2025

Contents		Page
Foreword		vi
1	Scope	1
2	Normative references	1
3	Terms, definitions, abbreviated terms and symbols	4
3.1	Terms and definitions	4
3.2	Abbreviated terms	6
3.3	Symbols	7
4	General	8
4.1	Dual normative references	8
4.2	Units of measurement	8
5	Information supplied by the purchaser	8
6	Manufacturing process	10
6.1	Melting practices	10
6.2	Product manufacturing process	10
6.3	Pipe end sizing	11
6.4	Straightening	11
6.5	Processes requiring validation	11
6.6	Traceability	12
6.7	Manufacturing procedure qualification test	12
6.8	Process for update of alloys and/or grades	12
7	Material requirements	12
7.1	Chemical composition	12
7.2	Tensile properties	13
7.3	Hardness properties	13
7.4	Charpy V-notch test properties — General requirements	13
7.4.1	Evaluation of test results	13
7.4.2	Critical thickness	13
7.4.3	Specimen size, orientation and hierarchy	13
7.4.4	Alternative size impact test specimens	14
7.4.5	Sub-size test specimens	14
7.4.6	Test temperature	14
7.5	Charpy V-notch — Absorbed energy requirements for coupling stock and accessory material — All grades	14
7.5.1	General	14
7.5.2	Requirements for all grades	14
7.6	Charpy V-notch — Absorbed energy requirements for pipe — All grades	15
7.7	Flattening requirements	16
7.8	Charpy V-notch test properties at low temperature for group 2	16
7.8.1	General	16
7.8.2	Evaluation of test results	16
7.8.3	Selection of test specimens	17
7.8.4	Test temperature	17
7.8.5	Absorbed energy requirements	17
7.9	Corrosion properties	17
7.9.1	General	17
7.9.2	Pitting corrosion properties for group 2	17
7.10	Microstructure properties	17
7.10.1	Group 1	17
7.10.2	Group 2	17

7.10.3	Groups 3 and 4.....	18
7.11	Surface condition.....	18
7.12	Defects.....	18
7.12.1	Pipe.....	18
7.12.2	Coupling stock and accessory material.....	19
7.12.3	Process control plan.....	19
8	Dimensions, masses and tolerances.....	19
8.1	Outside diameter, wall thickness and mass.....	19
8.2	Length.....	19
8.3	Tolerances.....	19
8.3.1	Tolerance on outside diameter, wall thickness and mass.....	19
8.3.2	Inside diameter, <i>d</i>	20
8.3.3	Straightness.....	20
8.3.4	Drift requirements.....	20
8.4	Product ends.....	20
9	Inspection and testing.....	20
9.1	Test equipment.....	20
9.2	Type and frequency of tests.....	20
9.3	Testing of chemical composition.....	20
9.3.1	Chemical analysis.....	20
9.3.2	Test method.....	21
9.3.3	Chromium depletion test — Groups 2, 3 and 4.....	21
9.4	Testing of mechanical characteristics.....	21
9.4.1	Test lot.....	21
9.4.2	Selection and preparation of samples and test pieces.....	21
9.5	Tensile test.....	21
9.5.1	Orientation and size of test pieces.....	21
9.5.2	Test method.....	21
9.5.3	Invalidation of test.....	22
9.5.4	Retest.....	22
9.6	Hardness test.....	22
9.6.1	Test pieces.....	22
9.6.2	Test method.....	22
9.6.3	Invalidation of tests.....	23
9.6.4	Periodic checks of hardness-testing machines.....	23
9.6.5	Verification of hardness-testing machines and indenters.....	24
9.6.6	Retests.....	25
9.7	Impact or flattening test.....	25
9.7.1	Test pieces.....	25
9.7.2	Frequency of testing.....	25
9.7.3	Impact test method.....	26
9.7.4	Flattening test method.....	26
9.7.5	Impact test retest.....	26
9.7.6	Flattening test retest.....	27
9.7.7	Invalidation of tests.....	27
9.8	Impact test at low temperature for group 2.....	27
9.9	Pitting corrosion test for group 2.....	27
9.10	Microstructural examination.....	28
9.10.1	Test pieces.....	28
9.10.2	Test method.....	28
9.10.3	Retest.....	29
9.11	Dimensional testing.....	29
9.11.1	General.....	29
9.11.2	Outside diameter.....	29
9.11.3	Wall thickness at end of products.....	29
9.11.4	Wall thickness of product body.....	30
9.12	Drift test.....	30
9.12.1	Non-upset and external upset pipe.....	30
9.12.2	Internal upset pipe.....	30
9.12.3	Drift mandrel coating.....	30

9.13	Length	30
9.14	Straightness	30
9.15	Mass determination	30
9.16	Visual inspection	30
9.16.1	General	30
9.16.2	Pipe body, coupling stock and accessory material	31
9.16.3	Pipe ends	31
9.16.4	Disposition	31
9.17	Non-destructive examination	31
9.17.1	General	31
9.17.2	NDE personnel	32
9.17.3	Products	32
9.17.4	Pup joints	32
9.17.5	Untested ends	32
9.17.6	Upset ends	33
9.17.7	Reference standards	33
9.17.8	NDE system capability records	33
9.17.9	All product group 1	34
9.17.10	Full-body NDE of product — Groups 2, 3 and 4	34
9.17.11	Pipe, coupling stock and accessory material requiring further evaluation	34
9.17.12	Evaluation of indications (prove-up)	35
9.17.13	Disposition of pipe containing defects	35
9.17.14	Disposition of coupling stock and accessory material containing defects	36
9.18	Positive material identification	37
10	Surface treatment	37
10.1	Group 1	37
10.2	Groups 2, 3 and 4	37
11	Marking	38
11.1	General	38
11.2	Colour-code identification	38
11.3	Marking content and sequence	38
11.4	Marking for couplings, pup joints and accessories after threading	39
12	Surface protection — Group 1	39
13	Documents	40
13.1	Electronic media	40
13.2	Retention of records	40
13.3	Test certificates	40
14	Handling, packaging and storage	41
14.1	General	41
14.2	Handling	41
14.3	Packaging	41
14.3.1	General	41
14.3.2	Identification	41
14.4	Storage	42
Annex A (normative)	Tables in SI units	43
Annex B (normative)	Figures in SI (USC) units	66
Annex C (normative)	Tables in USC units	71
Annex D (normative)	Purchaser inspection	94
Annex E (normative)	Cleanliness requirements	95
Annex F (normative)	Coupling blanks and accessory material from bar	97
Annex G (normative)	Product specification level 2 (PSL-2)	111
Annex H (normative)	Standardized manufacturing procedure qualification test	113
Annex I (informative)	Photographic examples of microstructures, groups 2, 3 and 4	117
	Bibliography	121