ISO 24203:2025-12 (E)

Oil and gas industries including lower carbon energy - Bulk material for offshore projects - Schedule for architectural doors

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Normative references 1

3 Terms and definitions 1

4 Design requirements for architectural doors 2
4.1 General information 2
4.1.1 Tag number 2
4.1.2 Room or area number 2
4.1.3 Room name 2
4.1.4 Drawing number 2
4.1.5 Internal or external door 2
4.1.6 Gastight door 2
4.1.7 Weathertight door 2
4.1.8 Fire rating 2
4.1.9 Blast overpressure 3
4.2 Door details 3
4.2.1 Clear opening and structure cut-out or wall cut-out 3
4.2.2 Opening operation 3
4.2.3 Frame fixing method 4
4.2.4 Door open direction 4
4.2.5 Leaf and frame material 5
4.2.6 Door finish method 5
4.2.7 Colour of door 5
4.2.8 Threshold type 6
4.2.9 Threshold height 6
4.2.10 Ventilation requirement 7
4.3 Accessories 8
4.3.1 Vision panel 8
4.3.2 Automatic closer 9
4.3.3 Hold open function 9
4.3.4 Doorstops 10
4.3.5 Magnetic door holder device 10
4.3.6 Panic bar 10
4.3.7 Kick plate and trolley protection plate 11
4.3.8 Flush bolts for double door 12
4.3.9 Eyebrow 13
4.3.10 Ramp 14
4.3.11 Other accessories 15
4.4 Locking system 16
4.4.1 Lock type 16
4.4.2 Padlock eye 16
4.4.3 Key side 17
4.5 Pneumatic system 17
4.5.1 General 17
4.5.2 Pneumatic key switch 17

4.5.3 Emergency air cylinder 18
4.5.4 Push button 19
4.5.5 Handle operation for pneumatic system 19
4.6 Other information 20
4.6.1 Noise rating 20
4.6.2 Mass of total door assembly 20

5 Schedule for architectural doors 20

5.1 General 20
5.2 Cabin 21
5.3 Office doors adjacent to a corridor 22
5.4 Private bathroom 23
5.5 Public toilet 24
5.6 Galley 26
5.7 Dining room 27
5.8 Laundry 28
5.9 Battery room 30
5.10 Uninterruptible power supply (UPS) 31
5.11 Workshop 32
5.12 Central control room (CCR) 34
5.13 High voltage room 35

Bibliography 37