ISO 24817:2026-09 (E)

Oil and gas industries including lower carbon energy - Composite repairs for piping - Qualification and design, installation, testing and integrity management

Contents

Page

Foreword vi

Introduction viii

1 Scope 1

2 Normative references 1

3 Terms and definitions 2

4 Symbols and abbreviated terms 7
4.1 Symbols 7
4.2 Abbreviated terms 10

5 Applications 11

6 Summary of key issues 13
6.1 General 13
6.2 Repair system qualification 13
6.3 Enquiry stage 13
6.4 Design of repair 13
6.4.1 General 13
6.4.2 Type A and Type B design cases 14
6.5 Installer training 15
6.6 Installation of repair 16
6.7 Ongoing integrity management of the repaired system 16

7 Qualification 16
7.1 Repair system qualification data 16
7.2 Re-qualification of the repair system 18
7.2.1 Overview 18
7.2.2 For Type A defect repairs 18
7.2.3 For Type B defect repairs 18

8 Repair feasibility assessment 18
8.1 General 18
8.2 Repair class 20
8.3 Required data 20
8.3.1 Background 20
8.3.2 Original equipment design data 20
8.3.3 Maintenance and operational histories 21
8.3.4 Service condition data 21

9 Design methodology 21
9.1 Design lifetime and initial service life 21
9.2 Environmental compatibility 22
9.3 Design temperature effects 23
9.4 Cyclic loading 24
9.5 Determination of design strains 24
9.5.1 General 24
9.5.2 Design strains based on default allowable strains 25

9.5.3 Design strains based on performance testing 25
9.6 Determination of equivalent load and equivalent pressure 25
9.7 Design of repairs for Type A defects 26
9.7.1 General 26
9.7.2 Design limited by substrate allowable stress 26
9.7.3 Design limited by composite laminate design strain, substrate shares loads 27
9.7.4 Design limited by composite laminate design strain, composite laminate carries all loads 28
9.8 Design of repairs for Type B defects 28
9.8.1 General 28

9.8.2 Determination of service factor, fleak 29
9.8.3 Circular or near-circular defects 29
9.8.4 Slot-type defects in the circumferential direction 29
9.8.5 Slot-type defects in the axial direction 30
9.9 External loads 31
9.10 Other defects (with assessments based on substrate stress) 31
9.11 Repair of other components 32
9.12 Axial extent of repair 33
9.12.1 General 33
9.12.2 Patches 34
9.13 Calculation of the composite laminate thickness, td 34
9.14 Confirmation that composite laminate thickness is within acceptable limits 34
9.14.1 General 34
9.14.2 Maximum acceptable value of td 35
9.14.3 Maximum allowable design pressure for tees or nozzles 35
9.14.4 Potential for repair disbonding 35
9.15 Calculation of total repair length 36
9.16 Design output 36
9.17 Optional design considerations 36
9.17.1 Fire performance 36
9.17.2 Cathodic disbonding 37
9.17.3 Electrical conductivity 37
9.17.4 Fretting type defects 37
9.17.5 Delamination or blister type defects 37
9.17.6 Clamps and other repair systems 37

10 Installation 38
10.1 Storage conditions 38
10.2 Documentation prior to repair application 38
10.2.1 Method statement 38
10.2.2 Work pack 39
10.3 Installer and supervisor qualifications 40
10.4 Installation procedure 40
10.5 Repair completion documentation 41
10.6 Live repairs 42
10.7 Repair of clamps, piping components, tanks, or vessels 43
10.8 Environmental considerations 43
10.9 Repair of defects within the repair system 43

11 Ongoing integrity management 43
11.1 General 43
11.2 Record keeping 44
11.3 In-service inspection 44
11.4 Allowable defects for the repair system 45
11.5 Repair system maintenance and remedial options 48
11.5.1 Overview 48
11.5.2 Substrate adjacent to the repair 49
11.5.3 Repairs to Type A defects 49
11.5.4 Repairs to Type B defects 49
11.5.5 Repair system 49
11.6 Repair lifetime considerations 50

11.6.1 Periodic review 50
11.6.2 Lifetime reduction 51
11.6.3 Lifetime extension 51
11.7 Modifications 51

12 System testing 51

13 Decommissioning 52

Annex A (informative) Design data sheet 53

Annex B (normative) Qualification data 56

Annex C (normative) Short-term pipe spool survival test 61

Annex D (normative) Measurement of LCL for through-wall defect calculation 63

Annex E (normative) Measurement of performance test data 68

Annex F (normative) Measurement of impact performance 70

Annex G (normative) Measurement of the degradation factor 71

Annex H (normative) Qualification of repair systems for other defects (with assessments based on substrate stress) 73

Annex I (informative) Guidance on the selection of the appropriate defect size and geometry for through-wall defects (Type B defect) 76

Annex J (normative) Installer qualification 89

Annex K (normative) Installation requirements and guidance 92

Annex L (informative) Design considerations 95

Annex M (informative) Management of the integrity of composite repair systems to piping and vessels 102

Bibliography 106