DIN EN ISO 24817:2026-12 (E)

Oil and gas industries including lower carbon energy - Composite repairs for piping - Qualification and design, installation, testing and integrity management (ISO 24817:2026); English version EN ISO 24817:2026

Contents

Page

Foreword ... **vi**

Introduction ... **viii**

1 Scope ... **1**

2 Normative references ... **1**

3 Terms and definitions ... **2**

4 Symbols and abbreviated terms ... **7**
4.1 Symbols ... 7
4.2 Abbreviated terms ... 10

5 Applications ... **11**

6 Summary of key issues ... **13**
6.1 General ... 13
6.2 Repair system qualification ... 13
6.3 Enquiry stage ... 13
6.4 Design of repair ... 13
6.4.1 General ... 13
6.4.2 Type A and Type B design cases ... 14
6.5 Installer training ... 15
6.6 Installation of repair ... 16
6.7 Ongoing integrity management of the repaired system ... 16

7 Qualification ... **16**
7.1 Repair system qualification data ... 16
7.2 Re-qualification of the repair system ... 18
7.2.1 Overview ... 18
7.2.2 For Type A defect repairs ... 18
7.2.3 For Type B defect repairs ... 18

8 Repair feasibility assessment ... **18**
8.1 General ... 18
8.2 Repair class ... 20
8.3 Required data ... 20
8.3.1 Background ... 20
8.3.2 Original equipment design data ... 20
8.3.3 Maintenance and operational histories ... 21
8.3.4 Service condition data ... 21

9 Design methodology ... **21**
9.1 Design lifetime and initial service life ... 21
9.2 Environmental compatibility ... 22
9.3 Design temperature effects ... 23
9.4 Cyclic loading ... 24
9.5 Determination of design strains ... 24
9.5.1 General ... 24
9.5.2 Design strains based on default allowable strains ... 25
9.5.3 Design strains based on performance testing ... 25

9.6 Determination of equivalent load and equivalent pressure 25
9.7 Design of repairs for Type A defects 26
9.7.1 General 26
9.7.2 Design limited by substrate allowable stress 26
9.7.3 Design limited by composite laminate design strain, substrate shares loads 27
9.7.4 Design limited by composite laminate design strain, composite laminate carries all loads 28
9.8 Design of repairs for Type B defects 28
9.8.1 General 28
9.8.2 Determination of service factor, f_{leak} 29
9.8.3 Circular or near-circular defects 29
9.8.4 Slot-type defects in the circumferential direction 29
9.8.5 Slot-type defects in the axial direction 30
9.9 External loads 31
9.10 Other defects (with assessments based on substrate stress) 31
9.11 Repair of other components 32
9.12 Axial extent of repair 33
9.12.1 General 33
9.12.2 Patches 34
9.13 Calculation of the composite laminate thickness, t_d 34
9.14 Confirmation that composite laminate thickness is within acceptable limits 34
9.14.1 General 34
9.14.2 Maximum acceptable value of t_d 35
9.14.3 Maximum allowable design pressure for tees or nozzles 35
9.14.4 Potential for repair disbonding 35
9.15 Calculation of total repair length 36
9.16 Design output 36
9.17 Optional design considerations 36
9.17.1 Fire performance 36
9.17.2 Cathodic disbonding 37
9.17.3 Electrical conductivity 37
9.17.4 Fretting type defects 37
9.17.5 Delamination or blister type defects 37
9.17.6 Clamps and other repair systems 37

10 Installation 38
10.1 Storage conditions 38
10.2 Documentation prior to repair application 38
10.2.1 Method statement 38
10.2.2 Work pack 39
10.3 Installer and supervisor qualifications 40
10.4 Installation procedure 40
10.5 Repair completion documentation 41
10.6 Live repairs 42
10.7 Repair of clamps, piping components, tanks, or vessels 43
10.8 Environmental considerations 43
10.9 Repair of defects within the repair system 43

11 Ongoing integrity management 43
11.1 General 43
11.2 Record keeping 44
11.3 In-service inspection 44
11.4 Allowable defects for the repair system 45
11.5 Repair system maintenance and remedial options 48
11.5.1 Overview 48
11.5.2 Substrate adjacent to the repair 49
11.5.3 Repairs to Type A defects 49
11.5.4 Repairs to Type B defects 49
11.5.5 Repair system 49

11.6 Repair lifetime considerations 50
11.6.1 Periodic review 50
11.6.2 Lifetime reduction 51
11.6.3 Lifetime extension 51
11.7 Modifications 51
12 System testing **51**
13 Decommissioning **52**
Annex A (informative) **Design data sheet** **53**
Annex B (normative) **Qualification data** **56**
Annex C (normative) **Short-term pipe spool survival test** **61**
Annex D (normative) **Measurement of γ_{LCL} for through-wall defect calculation** **63**
Annex E (normative) **Measurement of performance test data** **68**
Annex F (normative) **Measurement of impact performance** **70**
Annex G (normative) **Measurement of the degradation factor** **71**
Annex H (normative) **Qualification of repair systems for other defects (with assessments based on substrate stress)** **73**
Annex I (informative) **Guidance on the selection of the appropriate defect size and geometry for through-wall defects (Type B defect)** **76**
Annex J (normative) **Installer qualification** **89**
Annex K (normative) **Installation requirements and guidance** **92**
Annex L (informative) **Design considerations** **95**
Annex M (informative) **Management of the integrity of composite repair systems to piping and vessels** **102**
Bibliography **106**