

DIN EN ISO 24817:2026-12 (E)

Oil and gas industries including lower carbon energy - Composite repairs for piping - Qualification and design, installation, testing and integrity management (ISO 24817:2026); English version EN ISO 24817:2026

Contents

Page

Foreword.....	vi
Introduction.....	viii
1 Scope.....	1
2 Normative references.....	1
3 Terms and definitions.....	2
4 Symbols and abbreviated terms.....	7
4.1 Symbols.....	7
4.2 Abbreviated terms.....	10
5 Applications.....	11
6 Summary of key issues.....	13
6.1 General.....	13
6.2 Repair system qualification.....	13
6.3 Enquiry stage.....	13
6.4 Design of repair.....	13
6.4.1 General.....	13
6.4.2 Type A and Type B design cases.....	14
6.5 Installer training.....	15
6.6 Installation of repair.....	16
6.7 Ongoing integrity management of the repaired system.....	16
7 Qualification.....	16
7.1 Repair system qualification data.....	16
7.2 Re-qualification of the repair system.....	18
7.2.1 Overview.....	18
7.2.2 For Type A defect repairs.....	18
7.2.3 For Type B defect repairs.....	18
8 Repair feasibility assessment.....	18
8.1 General.....	18
8.2 Repair class.....	20
8.3 Required data.....	20
8.3.1 Background.....	20
8.3.2 Original equipment design data.....	20
8.3.3 Maintenance and operational histories.....	21
8.3.4 Service condition data.....	21
9 Design methodology.....	21
9.1 Design lifetime and initial service life.....	21
9.2 Environmental compatibility.....	22
9.3 Design temperature effects.....	23
9.4 Cyclic loading.....	24
9.5 Determination of design strains.....	24
9.5.1 General.....	24
9.5.2 Design strains based on default allowable strains.....	25
9.5.3 Design strains based on performance testing.....	25

9.6	Determination of equivalent load and equivalent pressure	25
9.7	Design of repairs for Type A defects	26
9.7.1	General	26
9.7.2	Design limited by substrate allowable stress	26
9.7.3	Design limited by composite laminate design strain, substrate shares loads	27
9.7.4	Design limited by composite laminate design strain, composite laminate carries all loads	28
9.8	Design of repairs for Type B defects	28
9.8.1	General	28
9.8.2	Determination of service factor, f_{leak}	29
9.8.3	Circular or near-circular defects	29
9.8.4	Slot-type defects in the circumferential direction	29
9.8.5	Slot-type defects in the axial direction	30
9.9	External loads	31
9.10	Other defects (with assessments based on substrate stress)	31
9.11	Repair of other components	32
9.12	Axial extent of repair	33
9.12.1	General	33
9.12.2	Patches	34
9.13	Calculation of the composite laminate thickness, t_d	34
9.14	Confirmation that composite laminate thickness is within acceptable limits	34
9.14.1	General	34
9.14.2	Maximum acceptable value of t_d	35
9.14.3	Maximum allowable design pressure for tees or nozzles	35
9.14.4	Potential for repair disbonding	35
9.15	Calculation of total repair length	36
9.16	Design output	36
9.17	Optional design considerations	36
9.17.1	Fire performance	36
9.17.2	Cathodic disbonding	37
9.17.3	Electrical conductivity	37
9.17.4	Fretting type defects	37
9.17.5	Delamination or blister type defects	37
9.17.6	Clamps and other repair systems	37
10	Installation	38
10.1	Storage conditions	38
10.2	Documentation prior to repair application	38
10.2.1	Method statement	38
10.2.2	Work pack	39
10.3	Installer and supervisor qualifications	40
10.4	Installation procedure	40
10.5	Repair completion documentation	41
10.6	Live repairs	42
10.7	Repair of clamps, piping components, tanks, or vessels	43
10.8	Environmental considerations	43
10.9	Repair of defects within the repair system	43
11	Ongoing integrity management	43
11.1	General	43
11.2	Record keeping	44
11.3	In-service inspection	44
11.4	Allowable defects for the repair system	45
11.5	Repair system maintenance and remedial options	48
11.5.1	Overview	48
11.5.2	Substrate adjacent to the repair	49
11.5.3	Repairs to Type A defects	49
11.5.4	Repairs to Type B defects	49
11.5.5	Repair system	49

11.6	Repair lifetime considerations.....	50
11.6.1	Periodic review.....	50
11.6.2	Lifetime reduction.....	51
11.6.3	Lifetime extension.....	51
11.7	Modifications.....	51
12	System testing.....	51
13	Decommissioning.....	52
Annex A (informative)	Design data sheet.....	53
Annex B (normative)	Qualification data.....	56
Annex C (normative)	Short-term pipe spool survival test.....	61
Annex D (normative)	Measurement of γ_{LCL} for through-wall defect calculation.....	63
Annex E (normative)	Measurement of performance test data.....	68
Annex F (normative)	Measurement of impact performance.....	70
Annex G (normative)	Measurement of the degradation factor.....	71
Annex H (normative)	Qualification of repair systems for other defects (with assessments based on substrate stress).....	73
Annex I (informative)	Guidance on the selection of the appropriate defect size and geometry for through-wall defects (Type B defect).....	76
Annex J (normative)	Installer qualification.....	89
Annex K (normative)	Installation requirements and guidance.....	92
Annex L (informative)	Design considerations.....	95
Annex M (informative)	Management of the integrity of composite repair systems to piping and vessels.....	102
Bibliography		106